

Order No.: 59TP1FN7 | **GTIN (EAN):** 4058352340288

Product description: Lic-infeed,L300,7x2.5²,IP64,wh



Licross® infeed, white; wiring trunking rail element of sheet steel, galvanised, coated, with cable entry for two cables, Ø 8.5..13mm; 2x end cap of PC, white, with cable entry for one cable, Ø 8.5..16mm; blank cover of PC/ABS, white; connector of steel, galvanised, connector pre-assembled on trunking rail; connection via terminal, 7-pole, 1.5..2.5mm², internal wiring halogen-free; dimension: (LxWxH) = 300 x 64 x 67mm; for protection rating IP50/IP54/IP64; insulation class: insulation class I (protective earthing); certification: CE, UKCA; packaging unit: 1 piece



Wt. (kg): 0.7
GTIN (EAN): 4058352340288

Order No.: 59TP1FN7 | **GTIN (EAN):** 4058352340288

Detailed technical description: Lic-infeed,L300,7x2.5²,IP64,wh



Key data

- Product type: infeed
- Product name: Licross®
- Order No.: 59TP1FN7

Lighting technology | Lamps | Control gear

Component 1

Lamps:

- Supplement: for connection on rail side

Component 2

Certificates, Standards

- Protection rating: for protection rating IP50/IP54/IP64
- Insulation class: insulation class I (protective earthing)
- Certification, designation: CE, UKCA

Material, Colour

- trunking rail element: sheet steel, galvanised, coated, white
- Colour specification: white
- end cap: PC, white
- Quantity: 2 piece
- Colour specification: white
- blank cover: PC/ABS, white
- Colour specification: white
- connector: steel, galvanised, connector pre-assembled on trunking rail

Electrical connection

- Connection: terminal, 7-pole, 1.5..2.5mm²
- Through-wiring: 7x 2.5mm²

Dimensions, Weight

- Length: 300mm
- Width: 64mm
- Height: 67mm
- Weight: 0.7kg