

Order No.: 56TL1FCSA | GTIN (EAN): 4058352373880

Product description: LicIntbasemod




Licross® InterfaceInterface S, slave, local control, central control, dimmable, installation location: to the Licross® trunking rail, of sheet steel, protection rating (complete): IP20, insulation class (complete): insulation class I (protective earthing), certification: CE, ENEC, VDE, UKCA, 1 x DALI-2, packaging unit: 1 piece



Wt. (kg): 0.5

GTIN (EAN): 4058352373880





Order No.: 56TL1FCSA | GTIN (EAN): 4058352373880

Detailed technical description: LicIntbasemod



Key data

- System family: Siteco Connect 11, SITECO Connect 22
- Product type: base module
- Product name: Licross® Interface
- Order No.: 56TL1FCSA

Lighting technology | Lamps | Control gear

Component 1

Lamps:

- Supplement: halogen-free wiring

Operating device:

- Control: DALI 2, dimmable

Certificates, Standards

- Protection rating: IP20
- Insulation class: insulation class I (protective earthing)
- Temperature range (operation): -20..+50°C
- Certification, designation: CE, ENEC, VDE, UKCA

Material, Colour

- trunking rail adapter set: sheet steel, coil coated, white
- Colour specification: white

Mounting

Supplement: only suitable for indoor

Electrical connection

Connection: plug, 5-pole, with phase selection

Dimensions, Weight

Length: 500mmWidth: 96mmHeight: 97mmWeight: 0.5kg

Outputs

DALI-2

 Feature: DALI, slave function, DALI current max. 6mA

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.de) Tolerances related to thermal, electrical and photometric data according to IEC 62722 Issued 05.01.2024 - Modifications and errors subject to change - Ensure that you always use the latest version -



Order No.: 56TL1FCSA | **GTIN (EAN):** 4058352373880

Dimensions: LicIntbasemod

