

## Order No.: 51TR6F7 | GTIN (EAN): 4058352242537 Product description: Lic,trunk.rail,L3000,7x2.52,sr



Licross®, trunking rail, of sheet steel, galvanised, coil coated, metallic grey (RAL 9006), length: 3.000 mm, width: 64 mm, height: 67mm, through-wiring: 7x 2.5mm², protection rating (complete): maximum IP64, depends on used inserts and accessories, insulation class (complete): insulation class I (protective earthing), certification: CE, UKCA, LABS conformity tested according to VDMA 24364:2018-05, packaging unit: 1 piece

 $\oplus$   $\in$ 

Wt. (kg): 4.7

GTIN (EAN): 4058352242537





## Order No.: 51TR6F7 | GTIN (EAN): 4058352242537

### **Detailed technical description:** Lic,trunk.rail,L3000,7x2.5<sup>2</sup>,sr



#### Key data

- Product type: trunking components group (TS)
- Product name: Licross®Order No.: 51TR6F7

# Lighting technology | Lamps | Control gear

#### **Component 1**

#### Lamps:

 Supplement: internal wiring halogenfree

#### Certificates, Standards

- Protection rating: maximum IP64, depends on used inserts and accessories
- Insulation class: insulation class I (protective earthing)
- Supplement: LABS conformity tested according to VDMA 24364:2018-05
- Certification, designation: CE, UKCA

#### Material, Colour

- trunking rail: sheet steel, galvanised, coil coated, metallic grey (RAL 9006)
- Colour specification: metallic grey (RAL 9006)

#### Mounting

- Mounting method, mounting location: suspended mounting, surfacemounted, to the ceiling
- Arrangement: single/continuous arrangement
- Supplement: only suitable for use in indoor areas

#### **Electrical connection**

Through-wiring: 7x 2.5mm²

#### **Dimensions, Weight**

Length: 3000mmWidth: 64mmHeight: 67mmWeight: 4.7kg



## Order No.: 51TR6F7 | GTIN (EAN): 4058352242537

**Dimensions:** Lic,trunk.rail,L3000,7x2.5²,sr

