

Order No.: 51DH11B73FF22 | **GTIN (EAN):** 4058352107270

Product description: Lun11mnRdSp,rec,nrrw,2780lm830,0/1,5p,sr





Lunis 11 mini round, Spot, downlight, LED rated luminous flux: 2.780lm, light colour: 830, with terminal, 5-pole, mains connection: 220..230V, AC, 50/60Hz, LED module, luminaire module, of diecast aluminium, coated, silver, diameter: 176mm, clamping range: 1..40mm, recessing ring, round, of PC, traffic white (RAL 9016), protection rating (complete): IP20, insulation class (complete): insulation class II (safety insulation), certification: CE, permissible ambient temperature for indoor applications: 0..+35°C, packaging unit: 1 piece

IP 20  

Lamps: LED
 Wt. (kg): 0.9
 GTIN (EAN): 4058352107270

4058352107270
 51DH11B73FF22

LED 3000K / CRI ≥ 80 ϕ_{N} 2780 lm



It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.de)

Tolerances related to thermal, electrical and photometric data according to IEC 62722

Issued 25.02.2023 - Modifications and errors subject to change - Ensure that you always use the latest version -

Order No.: 51DH11B73FF22 | GTIN (EAN): 4058352107270

Detailed technical description: Lun11mnRdSp,rec,nrrw,2780lm830,0/1,5p,sr



Key data

- Product type: downlight
- Product name: Lunis 11 mini round Spot
- Order No.: 51DH11B73FF22

Lighting technology | Lamps | Control gear

Component 1

Lighting technology:

- Beam angle: narrow distribution
- UGR viewing direction along lateral luminaire axis: ≤ 19

Lamps:

- Lamps: with High Power LED, LED
- Rated luminous flux: 2780lm
- Luminous efficacy: 102lm/W
- Colour temperature: 3000K
- Colour rendering index: CRI > 80
- Light colour: 830
- SDCM (Standard Deviation of Colour Matching): MacAdam ≤ 3 SDCM (initial)
- Rated input power: 27W

Operating device:

- Control: ON/OFF

Certificates, Standards

- Protection rating: IP20
- Insulation class: insulation class II (safety insulation)
- Temperature range (operation): 0..+35°C
- Certification, designation: CE

Material, Colour

- LED module: diecast aluminium, coated, silver
- luminaire module: diecast aluminium, coated, silver
- Colour specification: silver
- recessing ring: PC, traffic white (RAL 9016), round
- Colour specification: traffic white (RAL 9016)

Mounting

- Mounting method, mounting location: recessed, in the ceiling
- \varnothing of ceiling cut-out: 162mm
- Clamping range: 1..40mm
- Arrangement: single arrangement

Electrical connection

- Connection: terminal, 5-pole
- Nominal voltage: 220..230V, 50/60Hz, AC

Dimensions, Weight

- Diameter: 176mm
- Height: 175mm
- Weight: 0.9kg

Service life

- Rated service life: 50000h (L85/B50) at AT = 25°C

Order No.: 51DH11B73FF22 | GTIN (EAN): 4058352107270

Dimensions: Lun11mnRdSp,rec,nrrw,2780lm830,0/1,5p,sr



It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.de)

Tolerances related to thermal, electrical and photometric data according to IEC 62722


Issued 25.02.2023 - Modifications and errors subject to change - Ensure that you always use the latest version -

Order No.: 51DH11B73FF22 | GTIN (EAN): 4058352107270

Planning data: Lun11mnRdSp,rec,nrrw,2780lm830,0/1,5p,sr

**51DH11B73FF22: 1x LED
3000K / CRI ≥ 80**

4058352107270
51DH11B73FF22
LED 3000K / CRI ≥ 80 ϕ_N 2780 lm



I_{max} 3605 cd/klm at γ 0°

Luminance values (cd/m²)

C 0/180
L80 0
L70 0
L65 0

UGR 14.8 14.8
X 4H Y 8H ρ 70/50/20 S 0.25H

H(m)	ϕ (m)	$E_{max}(lx)$	$E_m(lx)$
2	0.87	2505	1918
3	1.31	1113	853
4	1.74	626	480
5	2.18	401	307
6	2.62	278	213

No. of luminaires in room


Lh(m)	Reflection factors 70/50/20					
	100		200		500	
2.5	2.5	3.0	2.5	3.0	2.5	3.0
3.0	0.7	0.8	1.3	1.6	3.4	3.9
4.0	1.8	1.6	3.6	3.1	9.1	7.9
5.0	2.0	1.8	3.9	3.7	9.8	9.1
7.5	2.6	2.3	5.2	4.7	13	12
10.0	4.3	3.7	8.6	7.4	22	19
15.0	4.9	4.5	9.7	8.9	24	22
20.0	23	21	46	42	115	106

Maintenance factor 0.8

Rh = Lh

**51DH11B73FF22 +
59DL1L0000G0000D0: 1x
LED 3000K / CRI ≥ 80**

4058352107270 + 4058352030165
51DH11B73FF22 + 59DL1L0000G0000D0
LED 3000K / CRI ≥ 80 ϕ_N 2910 lm



I_{max} 1764 cd/klm at γ 0°

Luminance values (cd/m²)

C 0/180
L80 0
L70 0
L65 0

UGR 14.7 14.7
X 4H Y 8H ρ 70/50/20 S 0.25H

H(m)	ϕ (m)	$E_{max}(lx)$	$E_m(lx)$
2	1.66	1284	969
3	2.49	571	431
4	3.31	321	242
5	4.14	205	155
6	4.97	143	108

No. of luminaires in room

Lh(m)	Reflection factors 70/50/20					
	100		200		500	
2.5	2.5	3.0	2.5	3.0	2.5	3.0
3.0	0.8	0.8	1.5	1.7	3.9	4.2
4.0	1.3	1.2	2.6	2.4	6.4	6.0
5.0	1.6	1.6	3.2	3.3	7.9	8.1
7.5	2.0	2.0	4.0	4.0	10	9.9
10.0	3.1	2.9	6.2	5.8	16	14
15.0	3.9	3.9	7.8	7.8	19	20
20.0	19	19	38	38	94	95

Maintenance factor 0.8

Rh = Lh

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.de)

Tolerances related to thermal, electrical and photometric data according to IEC 62722

Issued 25.02.2023 - Modifications and errors subject to change - Ensure that you always use the latest version -