

Order No.: 59TR1CX | GTIN (EAN): 4058352485385 Product description: Lic-X-conn,L300,IP40,wh(w/o.wiring)



Licross[®], X-connector, trunking rail element, of steel, galvanised, coated, white, length: 300mm, width: 300mm, height: 67mm, blank cover, of PC/ABS, white, connector, of steel, galvanised, protection rating (complete): for IP20/IP40 protection rating, certification: CE, UKCA, packaging unit: 1 piece

```
\in
```

Wt. (kg): 3.0 GTIN (EAN): 4058352485385

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.de) Tolerances related to thermal, electrical and photometric data according to IEC 62722 Issued 09.04.2025 - Modifications and errors subject to change - Ensure that you always use the latest version -

ѕітесо

Order No.: 59TR1CX | GTIN (EAN): 4058352485385 Detailed technical description: Lic-X-conn,L300,IP40,wh(w/o.wiring)



Key data

- Product type: X-connector
- Product name: Licross®
- Order No.: 59TR1CX

Certificates, Standards

- Protection rating: for IP20/IP40 protection rating
- Certification, designation: CE, UKCA

Material, Colour

- trunking rail element: steel, galvanised, coated, white
- Colour specification: white
- blank cover: PC/ABS, white
- Colour specification: white
- connector: steel, galvanised, connector pre-assembled on trunking rail
- Quantity: 4 piece

Mounting

 Supplement: with safety hook (with height adjustment), Ø 6mm, for suspension at central node

Dimensions, Weight

- Length: 300mm
- Width: 300mm
- Height: 67mm
- Weight: 3.0kg

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.de) Tolerances related to thermal, electrical and photometric data according to IEC 62722 Issued 09.04.2025 - Modifications and errors subject to change - Ensure that you always use the latest version -