

Order No.: 51HP32MB7MMA | GTIN (EAN): 4058352475669 Product description: HB42L,rot.sym,wd,90°,28000lm857,ML








Highbay 42-L, high bay luminaire, primary light control with lens, of PC, primary optical cover: cover panel, of PC, transparent, light emission: direct distribution, primary light characteristic: rotationally symmetric, installation type: suspended mounting, surface-mounted, LED, rated luminous flux: 28.000lm, luminous efficacy: 160lm/W, light colour: 857, colour temperature: 5700K, control gear: ON/OFF Multilumen, with cable, 3x 1.0mm², free wire ends, mains connection: 230V, AC, 50Hz, cable length: 1,5m, rated input power: 175W, housing, rotationally symmetric, of diecast aluminium, black, with hook on luminaire side, diameter: 305mm, height: 117mm, protection rating (complete): IP65, insulation class (complete): insulation class I (protective earthing), certification: CE, UKCA, protection symbol: D, impact resistance: IK08, permissible operating ambient temperature: -20..+40°C, corresponds to IFS (International Featured Standards) requirements for safety and quality in the food industry, packaging unit: 1 piece

Lamps: LED Wt. (kg): 2.4

GTIN (EAN): 4058352475669





Order No.: 51HP32MB7MMA | GTIN (EAN): 4058352475669

Detailed technical description: HB42L,rot.sym,wd,90°,28000lm857,ML



Key data

- Product type: high bay luminaire
- Product name: Highbay 42-L
- Order No.: 51HP32MB7MMA

Lighting technology | Lamps | Control gear

Component 1

Lighting technology:

- Light control: lens of PC
- Cover: cover panel, transparent
- Beam angle: wide distribution, 90°
- Symmetry: rotationally symmetric
- Light emission: direct distribution
- UGR viewing direction along longitudinal luminaire axis: ≥ 25
- UGR viewing direction along lateral luminaire axis: ≥ 25

Lamps:

- Lamps: with LED
- Rated luminous flux: 28000lm
- Luminous efficacy: 160lm/W
- Colour temperature: 5700K
- Colour rendering index: CRI > 80
- Light colour: 857
- SDCM (Standard Deviation of Colour Matching): MacAdam ≤ 6 SDCM (initial)
- Rated input power: 175W

Operating device:

- Control gear: ECG
- Control: ON/OFF Multilumen

Certificates, Standards

- Protection rating: IP65
- Insulation class: insulation class I (protective earthing)
- Impact resistance: IK08
- Protection symbol: D
- Temperature range (operation): -20..+40°C
- Supplement: corresponds to IFS (International Featured Standards) requirements for safety and quality in the food industry
- Certification, designation: CE, UKCA

Material, Colour

- housing: diecast aluminium, black, rotationally symmetric, with hook on luminaire side
- Quantity: 1 piece
- Colour specification: black
- Cover: cover panel of PC

Mounting

- Mounting method, mounting location: suspended mounting, surfacemounted, to the ceiling, to the chain
- Arrangement: single arrangement
- Supplement: only suitable for use in indoor areas, mounting accessories required, please order separately

Electrical connection

- Connection: cable, 3x 1.0mm², free wire ends
- Nominal voltage: 230V, 50Hz, AC

Dimensions, Weight

Diameter: 305mmHeight: 117mmWeight: 2.4kg

Service life

 Rated service life: 50000h (L80) at AT = 25°C



Order No.: 51HP32MB7MMA | GTIN (EAN): 4058352475669

Dimensions: HB42L,rot.sym,wd,90°,28000lm857,ML

