

Order No.: 5CL513613 | **GTIN (EAN):** 4058352521533


Product description: CL31Wall,rd,1x,300lm830,DA



CL 31 Wall, wall luminaire, primary light control with reflector, of aluminium, primary optical cover: cover panel, of glass, transparent, light emission: down distribution, primary light characteristic: symmetric, installation type: surface-mounted, for 1x LED, rated luminous flux: 300lm, luminous efficacy: 106lm/W, light colour: 830, colour temperature: 3000K, control gear: DALI, with terminal, 5-pole, max. 2.5mm², mains connection: 220..240V, AC, 50/60Hz, rated input power: 2.8W, luminaire housing, round, of aluminium, powder-coated, SITECO metallic grey, length: 143mm, width: 100mm, height: 186mm, protection rating (complete): IP65, insulation class (complete): insulation class I (protective earthing), certification: CE, ENEC, impact resistance: IK08, permissible operating ambient temperature for outdoor applications: -20..+50°C, packaging unit: 1 piece



Lamps:	1x LED
Wt. (kg):	1.7
GTIN (EAN):	4058352521533



Order No.: 5CL513613 | GTIN (EAN): 4058352521533

Detailed technical description: CL31Wall,rd,1x,300lm830,DA



Key data

- Product type: wall luminaire
- Product name: CL 31 Wall
- Order No.: 5CL513613

Lighting technology | Lamps | Control gear

Component 1

Lighting technology:

- Light control: reflector of aluminium
- Cover: cover panel, transparent
- Beam angle: medium distribution, 36°
- Symmetry: symmetric
- Light emission: down

Lamps:

- Lamps: with 1x LED
- Rated luminous flux: 1x 300lm
- Luminous efficacy: 106lm/W
- Colour temperature: 3000K
- Colour rendering index: CRI > 80
- Light colour: 830
- SDCM (Standard Deviation of Colour Matching): MacAdam ≤ 3 SDCM (initial)
- Rated input power: 2.8W

Operating device:

- Control gear: ECG DALI
- Control: DALI

Certificates, Standards

- Protection rating: IP65
- Insulation class: insulation class I (protective earthing)
- Impact resistance: IK08
- Temperature range (operation): -20..+50°C
- Certification, designation: CE, ENEC

Material, Colour

- luminaire housing: aluminium, powder-coated, SITECO metallic grey, round
- Cover: cover panel of glass

Mounting

- Mounting method, mounting location: surface-mounted, to the wall
- Supplement: SITECO Easy Concept mounting, SITECO Easy Concept installation

Electrical connection

- Connection: terminal, 5-pole, max. 2.5mm²
- Nominal voltage: 220..240V, 50/60Hz, AC

Dimensions, Weight

- Length: 143mm
- Width: 100mm
- Height: 186mm
- Weight: 1.7kg

Service life

- Rated service life: 65000h (L80/B50) at AT = 25°C

Order No.: 5CL513613 | GTIN (EAN): 4058352521533

Dimensions: CL31Wall,rd,1x,300lm830,DA

