

**Order No.:** 51TR6F5 | **GTIN (EAN):** 4058352265147


**Product description:** Lic, trunk.rail, L3000, 5x2.5<sup>2</sup>, sr



Licross®, trunking rail, of sheet steel, galvanised, coil coated, metallic grey (RAL 9006), length: 3.000 mm, width: 64 mm, height: 67mm, through-wiring: 5x 2.5mm<sup>2</sup>, protection rating (complete): maximum IP64, depends on used inserts and accessories, insulation class (complete): insulation class I (protective earthing), certification: CE, UKCA, LABS conformity tested according to VDMA 24364:2018-05, packaging unit: 1 piece



Wt. (kg): 4.6  
GTIN (EAN): 4058352265147



Order No.: 51TR6F5 | GTIN (EAN): 4058352265147

Detailed technical description: Lic,trunk.rail,L3000,5x2.5<sup>2</sup>,sr



#### Key data

- Product type: trunking components group (TS)
- Product name: Licross®
- Order No.: 51TR6F5

#### Lighting technology | Lamps | Control gear

#### Component 1

##### Lamps:

- Supplement: halogen-free wiring

##### Certificates, Standards

- Protection rating: maximum IP64, depends on used inserts and accessories
- Insulation class: insulation class I (protective earthing)
- Supplement: LABS conformity tested according to VDMA 24364:2018-05
- Certification, designation: CE, UKCA

##### Material, Colour

- trunking rail: sheet steel, galvanised, coil coated, metallic grey (RAL 9006)
- Colour specification: metallic grey (RAL 9006)

##### Mounting

- Mounting method, mounting location: suspended mounting, surface-mounted, to the ceiling
- Arrangement: single/continuous arrangement
- Supplement: only suitable for indoor use

##### Electrical connection

- Through-wiring: 5x 2.5mm<sup>2</sup>

##### Dimensions, Weight

- Length: 3000mm
- Width: 64mm
- Height: 67mm
- Weight: 4.6kg

Order No.: 51TR6F5 | GTIN (EAN): 4058352265147

Dimensions: Lic,trunk.rail,L3000,5x2.5<sup>2</sup>,sr

