

Order No.: 5DTAXTS42001 | GTIN (EAN): 4050737845203

Product description: AXT,3ph-tr,spsurf,gy,L2000,0/1



AX T, 3-phase track, installation type: suspended mounting, surface-mounted, mains connection: 220..240V/380..400V, AC, of extruded aluminium section, coated, grey, length: 2.000 mm, width: 32 mm, height: 33mm, protection rating (complete): IP20, insulation class (complete): insulation class I (protective earthing), certification: CE, ENEC, packaging unit: 1 piece

IP 20 ⊕ (∈

Wt. (kg): 1.6

GTIN (EAN): 4050737845203



Order No.: 5DTAXTS42001 | GTIN (EAN): 4050737845203

Detailed technical description: AXT,3ph-tr,spsurf,gy,L2000,0/1



Key data

Product type: 3-phase track

- Product name: AX T

- Order No.: 5DTAXTS42001

Lighting technology | Lamps | Control gear

Component 1

Lamps:

- Supplement: max. 16A

Operating device:

Control: ON/OFF

Certificates, Standards

- Protection rating: IP20

 Insulation class: insulation class I (protective earthing)

- Certification, designation: CE, ENEC

Material, Colour

- Colour specification: grey

Mounting

 Mounting method, mounting location: suspended mounting, surfacemounted, to the ceiling

Electrical connection

 Nominal voltage: 220..240V/380..400V, AC

Dimensions, Weight

Length: 2000mmWidth: 32mmHeight: 33mmWeight: 1.6kg