

Order No.: 5DTAXTS44002 | **GTIN (EAN):** 4058352112175

Product description: AXT,3ph-tr,spsurf,bk,L4000,0/1



AX T, 3-phase track, installation type: suspended mounting, surface-mounted, control gear: ON/OFF, mains connection: 220..240V/380..400V, AC, of extruded aluminium section, coated, jet black (RAL 9005), can be cut to preference, length: 4.000mm, width: 32mm, height: 33mm, protection rating (complete): IP20, insulation class (complete): insulation class I (protective earthing), certification: CE, ENEC, packaging unit: 1 piece

 IP 20  

Wt. (kg): 3.4
GTIN (EAN): 4058352112175

Order No.: 5DTAXTS44002 | GTIN (EAN): 4058352112175

Detailed technical description: AXT,3ph-tr,spsurf,bk,L4000,0/1



Key data

- Product type: 3-phase track
- Product name: AX T
- Order No.: 5DTAXTS44002

Lighting technology | Lamps | Control gear

Component 1

Lamps:

- Supplement: max. 16A

Operating device:

- Control: ON/OFF

Certificates, Standards

- Protection rating: IP20
- Insulation class: insulation class I (protective earthing)
- Certification, designation: CE, ENEC

Mounting

- Mounting method, mounting location: suspended mounting, surface-mounted, to the ceiling

Electrical connection

- Nominal voltage: 220..240V/380..400V, AC

Dimensions, Weight

- Length: 4000mm
- Width: 32mm
- Height: 33mm
- Weight: 3.4kg