

**Order No.:** 5XA5285LF14H | **GTIN (EAN):** 4058352835531

**Product description:** CL120iQ,bollard,P100007,1510lm740,SR



City-Light 120 iQ, bollard luminaire, Module 540 iQ-SR, primary light control with 3 zone faceted reflector, of plastic, silver coated, highly specular, structured, primary optical cover: cover, of PMMA, transparent, partly coated, light distribution: P100007, primary beam angle: extremely wide distribution, primary light characteristic: asymmetric, lamps: LED, rated values: 1.510lm | 10W | 151lm/W (begin service life); end service life: 1.510lm | 10,4W; at 50% lumin. flux: 755lm | 5,3W | 142,5lm/W, colour temperature: 4000K, colour rendering: CRI > 70, light colour: 740, light setting 1 (further light settings possible): 100% | 1.510lm | 10W | 151lm/W | 4.000K (begin service life); end service life: 10,4W, control gear: iQ Street-Remote, control: pre-setting: logarithmic dimming characteristic, Street-Remote, Auto-Match, Temp-Guard, Lumen-Switch, Night-Set, Smart-Wire, Light-Fading, Desk-Remote (wireless, voltage-free reading and setting of iQ features in the workshop via application-optimized NFC function/RFID function), optimised constant luminous flux control (CLO 2.0), mains connection: 220..240V, AC, 50/60Hz, surge voltage resistance: surge voltage resistance: 10kV (common mode); 6kV (differential mode), electrical connection: terminal, 6-pole, max. 2.5mm<sup>2</sup>, solid wire, fine wire, luminaire housing, cylindrical, of extruded aluminium section, coated, SITECO metallic grey (DB 702S), length: 1.200mm, diameter: 200mm, Module 540 iQ-SR, matt traffic white (RAL 9016), equipment: standard, protection rating (complete): IP54, insulation class (complete): insulation class II (safety insulation), certification: CE, ENEC, VDE, packaging unit: 1 piece



Lamps:	LED
Wt. (kg):	10.8
GTIN (EAN):	4058352835531



Order No.: 5XA5285LF14H | GTIN (EAN): 4058352835531

Detailed technical description: CL120iQ,bollard,P100007,1510lm740,SR



### Key data

- Product type: bollard luminaire
- Product name: City-Light 120 iQ
- Order No.: 5XA5285LF14H

### Lighting technology | Lamps | Control gear

#### Component 1

#### Lighting technology:

- Light control: 3 zone faceted reflector of plastic, silver coated, highly specular
- Cover: cover, transparent, partly coated
- Light distribution: P100007
- Beam angle: extremely wide distribution
- Symmetry: asymmetric distribution

#### Lamps:

- Lamps: with LED
- Rated values: 1510lm | 10W | 151lm/W (begin service life); end service life: 1510lm | 10.4W; at 50% lumin. flux: 755lm | 5.3W | 142.5lm/W
- Colour temperature: 4000K
- Colour rendering index: CRI > 70
- Light colour: 740
- SDCM (Standard Deviation of Colour Matching): MacAdam  $\leq$  5 SDCM (initial)

#### Factory light settings (LS):

- begin service life:  
LS 1: 100% | 1510lm | 10W | 151lm/W | 4000K
- end service life:  
LS 1: 10.4W
- further light settings possible

#### Operating device:

- Control gear: ECG iQ
- Control: iQ Street-Remote
- Equipment: optimised constant luminous flux control (CLO 2.0), Desk-Remote (wireless, voltage-free reading and setting of iQ features in the workshop via application-optimized NFC function/RFID function), Light-Fading, Smart-Wire, Night-Set, Lumen-Switch, Temp-Guard, Auto-Match, Street-Remote, pre-setting: logarithmic dimming characteristic

### Certificates, Standards

- Protection rating: IP54
- Insulation class: insulation class II (safety insulation)
- Certification, designation: CE, ENEC, VDE

### Material, Colour

- luminaire housing: extruded aluminium section, coated, SITECO metallic grey (DB 702S), cylindrical
- Module 540 iQ-SR: matt traffic white (RAL 9016)
- Cover: cover of PMMA

### Electrical connection

- Connection: terminal, 6-pole, max. 2.5mm<sup>2</sup>, solid wire, fine wire
- Nominal voltage: 220..240V, 50/60Hz, AC
- Surge voltage resistance: surge voltage resistance: 10kV (common mode); 6kV (differential mode)

### Dimensions, Weight


- Length: 1200mm
- Diameter: 200mm
- Weight: 10.8kg

### Service life

- Rated service life: 100000h at AT = 25°C

Order No.: 5XA5285LF14H | GTIN (EAN): 4058352835531

Dimensions: CL120iQ,bollard,P100007,1510lm740,SR



It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at [www.siteco.de](http://www.siteco.de))

Tolerances related to thermal, electrical and photometric data according to IEC 62722

Issued 14.03.2026 - Modifications and errors subject to change - Ensure that you always use the latest version -