

Order No.: 5EA1ECL02 | GTIN (EAN): 4058352768792

Product description: SConWi,GroupContrLE



SITECO Connect WirelessGroup Control LE, control unit, communication: 2.4GHz, 2G, 4G, 5G, LTE Cat M1, NB-IoT NB2, EGPRS, local mesh radio network, RS-485, control: Smart-Wire (control line), optionally via radio push button, with radio clock, digital input, via API, by AstroDim calendar, by weekday, by timer, by time, manual, local setting and operation with smartphone app, local setting and operation with USB stick, remote setup and operation, sensor technology: GALILEO, GLONASS, GNSS, GPS, operation only possible with external antenna, e.g. 5EA1EAT01 or 5EA1EAT02, Usage fees for remote access via web application and mobile network (LTE CAT M1 / NB IoT NB2 / EGPRS) are included in the scope of delivery, amounting to 60 credit points (= 60 months). This individually extendable term begins when the device's QR code is scanned into a system. The credit can then be used by other devices within the system, installation type: DIN rail mounting, installation location: in an electrical distributor, of plastic, voltage: 230V, voltage type: AC, RS-485, 3 x relay contact, protection rating (complete): IP20, certification: CE, packaging unit: 1 piece

IP 20 

Wt. (kg): 0.2
GTIN (EAN): 4058352768792

Order No.: 5EA1ECL02 | GTIN (EAN): 4058352768792

Detailed technical description: SConWi,GroupContrLE



Key data

- System family: SITECO Connect 31 Wireless
- Product type: control unit
- Product name: SITECO Connect Wireless
- Order No.: 5EA1ECL02

Lighting technology | Lamps | Control gear

Component 1

Operating device:

- Control: ON/OFF, operation only possible with external antenna, e.g. 5EA1EAT01 or 5EA1EAT02, Usage fees for remote access via web application and mobile network (LTE CAT M1 / NB IoT NB2 / EGPRS) are included in the scope of delivery, amounting to 60 credit points (= 60 months). This individually extendable term begins when the device's QR code is scanned into a system. The credit can then be used by other devices within the system
- Equipment: Smart-Wire

Certificates, Standards

- Protection rating: IP20
- Temperature range (operation): -25..+80°C
- Certification, designation: CE

Material, Colour

- housing: plastic, grey

Mounting

- Mounting method, mounting location: DIN rail mounting, in an electrical distributor

Electrical connection

- Nominal voltage: 230V, 50/60Hz, AC

Dimensions, Weight

- Length: 70mm
- Width: 60mm
- Height: 86mm
- Weight: 0.2kg