

Order No.: 5EA3TDC01 | **GTIN (EAN):** 4058352812044

Product description: SConWi,SmartPlugCasambi



SITECO Connect WirelessSmart Plug Casambi, luminaire controller, communication: 2.4GHz, Bluetooth, local mesh radio network, D4i type A, control: local setting and operation with smartphone app, manual, by daylight, optionally via radio push button, sensor technology: daylight sensor, configuration via Casambi app, Compatible only with ECGs with logarithmic DALI dimming curve, optional remote setup and operation via gateway, installation type: screw fastening, installation location: to the luminaire, Smart Interface above: Zhaga, Smart Interface below: Zhaga, of PBT, voltage: 12..20V, Bluetooth, protection rating (complete): IP66, certification: CE, UKCA, packaging unit: 1 piece

IP 66 IK 09 

Wt. (kg): 0.1
GTIN (EAN): 4058352812044

Order No.: 5EA3TDC01 | **GTIN (EAN):** 4058352812044

Detailed technical description: SConWi,SmartPlugCasambi



Key data

- System family: SITECO Connect
- Product type: luminaire controller
- Product name: SITECO Connect Wireless
- Order No.: 5EA3TDC01

Lighting technology | Lamps | Control gear

Component 1

Lamps:

- Rated input power: 0.2W

Operating device:

- Control: D4i, Casambi, configuration via Casambi app, Compatible only with ECGs with logarithmic DALI dimming curve, optional remote setup and operation via gateway

Certificates, Standards

- Protection rating: IP66
- Impact resistance: IK09
- Temperature range (operation): -40..+70°C
- Standard: according to Zhaga book 18
- Certification, designation: CE, UKCA

Material, Colour

- housing: PBT, transparent, colour-backed, transparent

Mounting

- Mounting method, mounting location: screw fastening, to the luminaire

Electrical connection

- Nominal voltage: 12..20V

Dimensions, Weight

- Weight: 0.1kg