

Order No.: 51SL627A45B | GTIN (EAN): 4058352865347

Product description: LicSp31,21°,5140lm940,0/1,sr



Licross® Spot 31, directional spotlight, light control with lens, of plastic, LED rated luminous flux: 5.140lm, light colour: 940, control gear: ECG, with plug, 3-pole, with phase selection, mains connection: 220..240V, AC, 50/60Hz, of aluminium, metallic grey (RAL 9006), length: 140mm, diameter: 90mm, protection rating (complete): IP20, insulation class (complete): insulation class I (protective earthing), certification: CE, packaging unit: 1 piece

IP 20  

Lamps:	LED
Wt. (kg):	1.2
GTIN (EAN):	4058352865347



Order No.: 51SL627A45B | GTIN (EAN): 4058352865347

Detailed technical description: LicSp31,21°,5140lm940,0/1,sr



#### Key data

- Product type: directional spotlight
- Product name: Licross® Spot 31
- Order No.: 51SL627A45B

#### Lighting technology | Lamps | Control gear

##### Component 1

#### Lighting technology:

- Light control: lens of plastic
- Beam angle: 21°
- Symmetry: symmetric

#### Lamps:

- Lamps: with LED
- Rated luminous flux: 5140lm
- Colour temperature: 4000K
- Colour rendering index: CRI > 90
- Light colour: 940
- SDCM (Standard Deviation of Colour Matching): MacAdam ≤ 3 SDCM (initial)
- Rated input power: 42.6W

#### Operating device:

- Control gear: ECG
- Control: ON/OFF

#### Certificates, Standards

- Protection rating: IP20
- Insulation class: insulation class I (protective earthing)
- Certification, designation: CE

#### Material, Colour

- Colour specification: metallic grey (RAL 9006)

#### Mounting

- Mounting method, mounting location: slip-in mounting, in the Licross® trunking rail

#### Electrical connection

- Connection: plug, 3-pole, with phase selection
- Nominal voltage: 220..240V, 50/60Hz, AC

#### Dimensions, Weight

- Length: 140mm
- Diameter: 90mm
- Height: 116mm
- Weight: 1.2kg

#### Service life

- Rated service life: 50000h (L80/B50) at AT = 25°C

Order No.: 51SL627A45B | GTIN (EAN): 4058352865347

Dimensions: LicSp31,21°,5140lm940,0/1,sr

