

**Order No.:** 51MX33DC4DSB | **GTIN (EAN):** 4058352893647


**Product description:** Sil21,ELD-P,14790lm840,DA2,L3004,sr,sp



Silica® 21, office luminaire, primary optical cover: prismatic diffuser, of PMMA, CAT 2 ( $L \leq 3000 \text{cd/m}^2$ ), light emission: direct/indirect distribution, primary light characteristic: symmetric, installation type: suspended mounting, LED, rated luminous flux: 14.790lm, luminous efficacy: 158lm/W, light colour: 840, colour temperature: 4000K, with terminal, 3+2-pole, max. 2.5mm<sup>2</sup>, mains connection: 220..240V, AC, 50/60Hz, rated input power: 93.9W, luminaire housing, of aluminium, metallic grey (RAL 9006), length: 3.004mm, width: 53mm, height: 53mm, protection rating (complete): IP20, insulation class (complete): insulation class I (protective earthing), certification: CE, permissible operating ambient temperature: 0..+35°C, standard: EN 50419, packaging unit: 1 piece

IP 20  

Lamps:	LED
Wt. (kg):	5.5
GTIN (EAN):	4058352893647



**Order No.:** 51MX33DC4DSB | **GTIN (EAN):** 4058352893647

**Detailed technical description:** Sil21,ELD-P,14790lm840,DA2,L3004,sr,sp



#### Key data

- Product type: office luminaire
- Product name: Silica® 21
- Order No.: 51MX33DC4DSB

#### Lighting technology | Lamps | Control gear

##### Component 1

#### Lighting technology:

- Cover: prismatic diffuser
- Beam angle: extremely wide distribution
- Symmetry: symmetric
- Light emission: direct/indirect distribution
- UGR viewing direction along longitudinal luminaire axis:  $\leq 19$
- UGR viewing direction along lateral luminaire axis:  $\leq 19$

#### Lamps:

- Lamps: with LED
- Rated luminous flux: 14790lm
- Luminous efficacy: 158lm/W
- Colour temperature: 4000K
- Colour rendering index: CRI > 80
- Light colour: 840
- SDCM (Standard Deviation of Colour Matching): MacAdam  $\leq 3$  SDCM (initial)
- Rated input power: 93.9W

#### Operating device:

- Control: DALI 2

#### Certificates, Standards

- Protection rating: IP20
- Insulation class: insulation class I (protective earthing)
- Temperature range (operation): 0..+35°C
- Standard: EN 50419
- Certification, designation: CE

#### Material, Colour

- luminaire housing: aluminium, metallic grey (RAL 9006)
- Colour specification: metallic grey (RAL 9006)
- Cover: prismatic diffuser of PMMA

#### Mounting

- Mounting method, mounting location: suspended mounting
- Arrangement: single arrangement

#### Electrical connection

- Connection: terminal, 3+2-pole, max. 2.5mm<sup>2</sup>
- Nominal voltage: 220..240V, 50/60Hz, AC

#### Dimensions, Weight

- Length: 3004mm
- Width: 53mm
- Height: 53mm
- Weight: 5.5kg

#### Service life

- Rated service life: 70000h (L80/B50) at AT = 25°C, 50000h (L85/B50) at AT = 25°C

Order No.: 51MX33DC4DSB | GTIN (EAN): 4058352893647

Dimensions: Sil21,ELD-P,14790lm840,DA2,L3004,sr,sp



It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at [www.siteco.de](http://www.siteco.de))  
Tolerances related to thermal, electrical and photometric data according to IEC 62722  
Issued 08.03.2024 - Modifications and errors subject to change - Ensure that you always use the latest version -