

Order No.: 5XCMOD1C2DC | GTIN (EAN): 4058352391884 Product description: SL11,Plusmc,LEDmod,P1.0a,722



Streetlight SL 11 Plus micro, LED module, primary light control with cycle path optic, light distribution: P1.0a, primary light characteristic: asymmetric, High Power LED, light colour: 722, colour temperature: 2200K, mains connection: 230V, 50Hz, LED module, protection rating (complete): as luminaire, packaging unit: 1 piece

Wt. (kg): 0.3 GTIN (EAN): 405

0.3 4058352391884

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.de) Tolerances related to thermal, electrical and photometric data according to IEC 62722 Issued 09.02.2024 - Modifications and errors subject to change - Ensure that you always use the latest version -

ѕітесо

Order No.: 5XCMOD1C2DC | GTIN (EAN): 4058352391884 Detailed technical description: SL11,Plusmc,LEDmod,P1.0a,722



- Product type: LED module
 Product name: Streetlight SL 11 Plus
 - micro
- Order No.: 5XCMOD1C2DC

Lighting technology | Lamps | Control gear

Component 1

Lighting technology:

- Light control: cycle path optic
- Light distribution: P1.0a
- Beam angle: extremely wide distribution
- Symmetry: asymmetric distribution

Lamps:

- Lamps: with High Power LED
- Colour temperature: 2200K
- Colour rendering index: CRI > 70
- Light colour: 722

Certificates, Standards

- Protection rating: as luminaire

Electrical connection

- Nominal voltage: 230V, 50Hz

Dimensions, Weight

- Weight: 0.3kg

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.de) Tolerances related to thermal, electrical and photometric data according to IEC 62722 Issued 09.02.2024 - Modifications and errors subject to change - Ensure that you always use the latest version -