

**Order No.:** 5XCMOD1A3DC | **GTIN (EAN):** 4058352391808

**Product description:** SL11,Plusmc,LEDmod,ST1.2a,830



Streetlight SL 11 Plus micro, LED module, light distribution: ST1.2a, primary light characteristic: asymmetric, High Power LED, light colour: 830, colour temperature: 3000K, mains connection: 230V, 50Hz, LED module, protection rating (complete): as luminaire, packaging unit: 1 piece

Wt. (kg): 0.2  
GTIN (EAN): 4058352391808

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at [www.siteco.de](http://www.siteco.de))  
Tolerances related to thermal, electrical and photometric data according to IEC 62722  
Issued 23.05.2025 - Modifications and errors subject to change - Ensure that you always use the latest version -

**Order No.:** 5XCMOD1A3DC | **GTIN (EAN):** 4058352391808

**Detailed technical description:** SL11,Plusmc,LEDmod,ST1.2a,830



#### **Key data**

- Product type: LED module
- Product name: Streetlight SL 11 Plus micro
- Order No.: 5XCMOD1A3DC

#### **Lighting technology | Lamps | Control gear**

##### **Component 1**

###### **Lighting technology:**

- Light distribution: ST1.2a
- Beam angle: wide distribution
- Symmetry: asymmetric distribution

###### **Lamps:**

- Lamps: with High Power LED
- Colour temperature: 3000K
- Colour rendering index: CRI > 80
- Light colour: 830

###### **Certificates, Standards**

- Protection rating: as luminaire

###### **Electrical connection**

- Nominal voltage: 230V, 50Hz

###### **Dimensions, Weight**

- Weight: 0.2kg

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at [www.siteco.de](http://www.siteco.de))  
Tolerances related to thermal, electrical and photometric data according to IEC 62722  
Issued 23.05.2025 - Modifications and errors subject to change - Ensure that you always use the latest version -