

Order No.: 59TL1CN0 | GTIN (EAN): 4058352957486 Product description: Lic-conn.comp.centr,L650,IP40,wh



Licross[®] connection compartment central, white; connection compartment central of sheet steel, galvanised, coated, with cable entry for six cables, Ø 8.5..13mm; 2x connector of steel, galvanised2x blank cover of PC/ABS, white; dimension: (LxWxH) = 650 x 64 x 67mm; for IP20/IP40 protection rating; insulation class: insulation class I (protective earthing); certification: CE, UKCA; packaging unit: 1 piece

⊕ (€

Wt. (kg): 1.4 GTIN (EAN): 4058352957486

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.de) Tolerances related to thermal, electrical and photometric data according to IEC 62722 Issued 09.04.2025 - Modifications and errors subject to change - Ensure that you always use the latest version -

ѕітесо

Order No.: 59TL1CN0 | GTIN (EAN): 4058352957486 Detailed technical description: Lic-conn.comp.centr,L650,IP40,wh



Key data

- Product type: junction box
- Product name: Licross®
- Order No.: 59TL1CN0

Certificates, Standards

- Protection rating: for IP20/IP40 protection rating
- Insulation class: insulation class I (protective earthing)
- Certification, designation: CE, UKCA

Material, Colour

- connection compartment central: sheet steel, galvanised, coated, white
- Colour specification: white
- connector: steel, galvanised, connector pre-assembled on trunking rail
- Quantity: 2 piece
- blank cover: PC/ABS, white
- Quantity: 2 piece
- Colour specification: white

Dimensions, Weight

- Length: 650mm
- Width: 64mm
- Height: 67mm
- Weight: 1.4kg

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.de) Tolerances related to thermal, electrical and photometric data according to IEC 62722 Issued 09.04.2025 - Modifications and errors subject to change - Ensure that you always use the latest version -