siteco

Order No.: 5XA76724B30C | **GTIN (EAN):** 4058352469538

Product description: FL20mn,ECGunit,PlusDA,96W,IC2

Floodlight FL 20 mini, ECG unit, control gear: Plus/DALI, rated input power: 96W, ECG unit, DALI, insulation class (complete): insulation class II (safety insulation), certification: CE, packaging unit: 1 piece

Wt. (kg):	0.9
GTIN (EAN):	4058352469538

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.de)
Tolerances related to thermal, electrical and photometric data according to IEC 62722
Issued 14.02.2026 - Modifications and errors subject to change - Ensure that you always use the latest version -

Siteco GmbH • Georg-Simon-Ohm-Str. 50 • 83301 Traunreut, Germany • Tel +49(8669)33-0 • Fax +49(8669)33-397 • eMail info@siteco.de • Internet www.siteco.com

siteco

Order No.: 5XA76724B30C | **GTIN (EAN):** 4058352469538

Detailed technical description: FL20mn,ECGunit,PlusDA,96W,IC2

Key data
- Product type: ECG unit
- Product name: Floodlight FL 20 mini
- Order No.: 5XA76724B30C

Lighting technology | Lamps | Control gear

Component 1

Lamps:
- Rated input power: 96W

Operating device:
- Control gear: ECG Plus
- Control: Plus/DALI

Certificates, Standards
- Insulation class: insulation class II (safety insulation)
- Certification, designation: CE

Electrical connection
- Surge voltage resistance: 10kV 1.2/50µs

Dimensions, Weight
- Weight: 0.9kg

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.de)
Tolerances related to thermal, electrical and photometric data according to IEC 62722
Issued 14.02.2026 - Modifications and errors subject to change - Ensure that you always use the latest version -

Siteco GmbH • Georg-Simon-Ohm-Str. 50 • 83301 Traunreut, Germany • Tel +49(8669)33-0 • Fax +49(8669)33-397 • eMail info@siteco.de • Internet www.siteco.com