

Order No.: 5XA7662A0000C | **GTIN (EAN):** 4058352230572

Product description: FL20mc,hous,Plus,27W,IC2



Floodlight FL 20 micro, housing, primary light characteristic: asymmetric, control gear: Plus, mains connection: 220..240V, AC, rated input power: 27W, housing frame, housing, of diecast aluminium, powder-coated, SITECO metallic grey (DB 702S), incl. 1x M20 cable gland for cable Ø 6.5..12mm, length: 304mm, width: 222mm, height: 55mm, DALI, protection rating (complete): IP66, insulation class (complete): insulation class II (safety insulation), certification: CE, packaging unit: 1 piece

IP 66  

Wt. (kg): 1.7
GTIN (EAN): 4058352230572

Order No.: 5XA7662A0000C | **GTIN (EAN):** 4058352230572

Detailed technical description: FL20mc,hous,Plus,27W,IC2



Key data

- Product type: housing
- Product name: Floodlight FL 20 micro
- Order No.: 5XA7662A0000C

Lighting technology | Lamps | Control gear

Component 1

Lighting technology:

- Symmetry: asymmetric distribution

Lamps:

- Rated input power: 27W

Operating device:

- Control gear: ECG Plus
- Control: Plus

Certificates, Standards

- Protection rating: IP66
- Insulation class: insulation class II (safety insulation)
- Certification, designation: CE

Material, Colour

- housing frame: diecast aluminium, powder-coated, SITECO metallic grey (DB 702S), incl. 1x M20 cable gland for cable Ø 6.5..12mm
- housing: diecast aluminium, powder-coated, SITECO metallic grey (DB 702S), incl. 1x M20 cable gland for cable Ø 6.5..12mm
- Colour specification: SITECO metallic grey (DB 702S)

Electrical connection

- Nominal voltage: 220..240V, AC

Dimensions, Weight

- Length: 304mm
- Width: 222mm
- Height: 55mm
- Weight: 1.7kg