

Order No.: 5EA40RSP01 | **GTIN (EAN):** 4069025279408

Product description: SConWi,MotRad.D



SITECO Connect Wireless Motion Radar Down, sensor, communication: D4i type B, control: local setting and operation with USB stick, by movement, sensor technology: 1 radar movement sensor, Smart Interface below, without built-in radio device, installation type: screw fastening, installation location: to the luminaire, of plastic, voltage: 24V, voltage type: DC, radar movement sensor, protection rating (complete): IP66, certification: CE, packaging unit: 1 piece

IP 66 IK 09 CE

Wt. (kg): 0.1
GTIN (EAN): 4069025279408

Order No.: 5EA40RSP01 | **GTIN (EAN):** 4069025279408

Detailed technical description: SConWi,MotRad.D



Key data

- System family: SITECO Connect 31 Wireless
- Product type: sensor
- Product name: SITECO Connect Wireless
- Order No.: 5EA40RSP01

Lighting technology | Lamps | Control gear

Component 1

Operating device:

- Control: D4i, Smart Interface below, without built-in radio device

Certificates, Standards

- Protection rating: IP66
- Impact resistance: IK09
- Temperature range (operation): -30...+85°C
- Standard: according to Zhaga book 18
- Certification, designation: CE

Material, Colour

- housing: plastic, transparent, colour-backed, transparent
- Colour specification: transparent

Mounting

- Mounting method, mounting location: screw fastening, to the luminaire
- Mounting height: 4...8m

Electrical connection

- Nominal voltage: 24V, DC

Dimensions, Weight

- Diameter: 80mm
- Height: 49mm
- Weight: 0.1kg

Inputs

radar movement sensor


- Detection range: max. 16x8m

Order No.: 5EA40RSP01 | **GTIN (EAN):** 4069025279408


Dimensions: SConWi,MotRad.D

Motion Radar Down 5EA40RSP01

Side view



Top view



Mounting height
5m

X-Axis
 $\varnothing = 16\text{m}$

Y-Axis
 $\varnothing = 8\text{m}$

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.de)

Tolerances related to thermal, electrical and photometric data according to IEC 62722

Issued 09.04.2025 - Modifications and errors subject to change - Ensure that you always use the latest version -