

Order No.: 5XA1565E1V3 | **GTIN (EAN):** 4069025123343

Product description: GT,ST1.2a,730,asy,cvr.pan,TSG,transp



electrics components group, for Large Bell iQ, LED luminous flux: 4.750 lm, colour temperature: 3000K, mains connection: 220..240V, AC, 50/60Hz, start of lifetime: 34 W, end of service life: 38 W, reduction: 16 W, primary light characteristic: asymmetric, primary optical cover: cover panel, of toughened safety glass, transparent, gear tray with cover, insulation class (complete): insulation class II (safety insulation), certification: CE, ENEC, VDE



Lamps:	LED
Wt. (kg):	4.0
GTIN (EAN):	4069025123343

Order No.: 5XA1565E1V3 | **GTIN (EAN):** 4069025123343

Detailed technical description: GT,ST1.2a,730,asy,cvr.pan,TSG,transp

Key data

- Product type: electrics components group
- Product name: Large Bell iQ
- Order No.: 5XA1565E1V3

Lighting technology | Lamps | Control gear

Component 1

Lighting technology:

- Light control: 3 zone faceted reflector of plastic, silver coated
- Cover: cover panel, transparent
- Light distribution: ST1.2a
- Beam angle: wide distribution
- Symmetry: asymmetric distribution

Lamps:

- Lamps: with High Power LED, LED
- Rated luminous flux: 4750lm
- Luminous efficacy: 139lm/W
- Colour temperature: 3000K
- Colour rendering index: CRI > 70
- Light colour: 730
- Rated input power begin service life: 34
- Rated input power end service life: 38
- Rated input power at 50% lumin. flux: 16

Operating device:

- Control: iQ-Street Remote, D4i with power reduction, Smart Interface above
- Equipment: optimised constant luminous flux control (CLO 2.0), Desk-Remote (wireless, voltage-free reading and setting of iQ features in the workshop via application-optimized NFC function/RFID function), Light-Fading, Smart-Wire, Night-Set, Lumen-Switch, Temp-Guard, Auto-Match, Street-Remote, pre-setting: logarithmic dimming characteristic

Certificates, Standards

- Insulation class: insulation class II (safety insulation)
- Certification, designation: CE, ENEC, VDE

Material, Colour

- Cover: cover panel of toughened safety glass

Electrical connection

- Nominal voltage: 220..240V, 50/60Hz, AC
- Surge voltage resistance: surge voltage resistance: 10kV (common mode); 6kV (differential mode)

Dimensions, Weight

- Weight: 4.0kg

Light emission

- Light emission: < 3%

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.de)

Tolerances related to thermal, electrical and photometric data according to IEC 62722

Issued 09.04.2025 - Modifications and errors subject to change - Ensure that you always use the latest version -