

**Order No.:** 5XA769LEDUNITB2 | **GTIN (EAN):** 4069025289353

**Product description:** FL20mx,LED-unit,RS17,740,chlor.resist



Floodlight FL 20 maxi, LED unit, primary light control with lens, of PMMA, primary optical cover: cover panel, of toughened safety glass, transparent, light distribution: RS17, light emission: direct distribution, primary light characteristic: asymmetric, installation type: screw fastening, LED, High Power LED, light colour: 740, colour temperature: 4000K, with cable with plug, AC, 50/60Hz, LED unit, of diecast aluminium, powder-coated, SITECO metallic grey (DB 702S), length: 662mm, width: 298mm, height: 106mm, protection rating (complete): IP66, certification: CE, packaging unit: 1 piece

IP 66 CE

Lamps:	LED
Wt. (kg):	6.4
GTIN (EAN):	4069025289353

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at [www.siteco.de](http://www.siteco.de))  
Tolerances related to thermal, electrical and photometric data according to IEC 62722  
Issued 30.10.2025 - Modifications and errors subject to change - Ensure that you always use the latest version -

**Order No.:** 5XA769LEDUNITB2 | **GTIN (EAN):** 4069025289353

**Detailed technical description:** FL20mx,LED-unit,RS17,740,chlor.resist



#### **Key data**

- Product type: LED unit
- Product name: Floodlight FL 20 maxi
- Order No.: 5XA769LEDUNITB2

#### **Lighting technology | Lamps | Control gear**

##### **Component 1**

###### **Lighting technology:**

- Light control: lens of PMMA
- Cover: cover panel, transparent
- Light distribution: RS17
- Symmetry: asymmetric distribution
- Light emission: direct distribution

###### **Lamps:**

- Lamps: High Power LED, LED
- Colour temperature: 4000K
- Colour rendering index: CRI > 70
- Light colour: 740

#### **Certificates, Standards**

- Protection rating: IP66
- Certification, designation: CE

#### **Material, Colour**

- LED unit: diecast aluminium, powder-coated, SITECO metallic grey (DB 702S)
- Colour specification: SITECO metallic grey (DB 702S)
- Cover: cover panel of toughened safety glass

#### **Mounting**

- Mounting method, mounting location: screw fastening, in housing

#### **Electrical connection**

- Connection: cable with plug

#### **Dimensions, Weight**

- Length: 662mm
- Width: 298mm
- Height: 106mm
- Weight: 6.4kg

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at [www.siteco.de](http://www.siteco.de))  
Tolerances related to thermal, electrical and photometric data according to IEC 62722  
Issued 30.10.2025 - Modifications and errors subject to change - Ensure that you always use the latest version -