ѕітесо

Order No.: 58DC011M04400A | GTIN (EAN): 4069025314178 Product description: LunR,LI,wd,4310Im840,ML





Lunis R, luminaire insert, rated luminous flux: 4.310lm, light colour: 840, control gear: ON/OFF Multilumen, mains connection: 220..240V, AC, 50/60Hz, rated input power: 25.9W, primary light control with lens, of plastic, primary optical cover: cover, of PMMA, light emission: direct distribution, protection rating (complete): IP20, certification: CE, packaging unit: 1 piece

IP 20 (E

Wt. (kg): 0.5 GTIN (EAN): 4069025314178

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.de) Tolerances related to thermal, electrical and photometric data according to IEC 62722 Issued 11.04.2025 - Modifications and errors subject to change - Ensure that you always use the latest version -

ѕітесо

Order No.: 58DC011M04400A | GTIN (EAN): 4069025314178 Detailed technical description: LunR,LI,wd,4310Im840,ML



Key data

- Product type: luminaire insert
- Product name: Lunis R
- Order No.: 58DC011M04400A

Lighting technology | Lamps | Control gear

Component 1

Lighting technology:

- Light control: lens of plastic
- Cover: cover
- Beam angle: wide distribution
- Light emission: direct distribution

Lamps:

- Rated luminous flux: 4310lm
- Luminous efficacy: 166lm/W
- Colour temperature: 4000K
- Colour rendering index: CRI > 80
- Light colour: 840
- Rated input power: 25.9W

Operating device:

Control: ON/OFF Multilumen

Certificates, Standards

- Protection rating: IP20
- Certification, designation: CE

Material, Colour

- Quantity: 1 piece
- Cover: cover of PMMA

Mounting

- Arrangement: single arrangement

Electrical connection

 Nominal voltage: 220..240V, 50/60Hz, AC

Dimensions, Weight

- Weight: 0.5kg