

**Order No.:** 51TD16DN6EXMD | **GTIN (EAN):** 4069025003300

**Product description:** Lic11Pe,wd,14180lm865,DA2,IP54,L1500,wh



Licross® 11 Performance HO, luminaire insert, of sheet steel, galvanised, coil coated, white, length: 1.500mm, width: 120mm, height: 123mm, LED rated luminous flux: 14.180lm, light colour: 865, control gear: DALI 2 (for two DALI lines), with plug, 6-pole, with phase selection, mains connection: 220..240V, AC/DC, 0/50..60Hz, rated input power: 81W, internal wiring halogen-free, for central battery installations according to DIN EN 60598-2-22, for emergency light function, without changeover relay, primary light control with lens, of plastic, primary optical cover: cover, of PMMA, light emission: direct/indirect distribution, primary light characteristic: symmetric, protection rating (complete): IP54, insulation class (complete): insulation class I (protective earthing), certification: CE, ENEC, VDE, UKCA, protection symbol: D if used in an environment with non-conductive dust loads with corresponding accessories, impact resistance: IK06, permissible ambient temperature for indoor applications: -25..+35°C, standard: EN 60598-2-22, corresponds to IFS (International Featured Standards) requirements for safety and quality in the food industry, reducing of maximum allowable ambient temperature of 5°C with ceiling mounting, LABS conformity tested according to VDMA 24364:2018-05, packaging unit: 1 piece



Lamps:	LED
Wt. (kg):	3.1
GTIN (EAN):	4069025003300



**Order No.:** 51TD16DN6EXMD | **GTIN (EAN):** 4069025003300

**Detailed technical description:** Lic11Pe,wd,14180lm865,DA2,IP54,L1500,wh



## Key data

- Product type: luminaire insert
- Product name: Licross® 11 Performance HO
- Order No.: 51TD16DN6EXMD

## Lighting technology | Lamps | Control gear

### Component 1

#### Lighting technology:

- Light control: lens of plastic
- Cover: cover
- Beam angle: wide distribution
- Symmetry: symmetric
- Light emission: direct/indirect distribution, 80:20
- UGR viewing direction along longitudinal luminaire axis:  $\leq 19$
- UGR viewing direction along lateral luminaire axis:  $\leq 25$

#### Lamps:

- Lamps: with LED
- Rated luminous flux: 14180lm
- Luminous efficacy: 174lm/W
- Colour temperature: 6500K
- Colour rendering index: CRI  $> 80$
- Light colour: 865
- SDCM (Standard Deviation of Colour Matching): MacAdam  $\leq 2$  SDCM (initial)
- Rated input power: 81W
- Supplement: without changeover relay, for emergency light function, for central battery installations according to DIN EN 60598-2-22, internal wiring halogen-free

#### Operating device:

- Control: DALI 2 (for two DALI lines)

## Certificates, Standards

- Protection rating: IP54
- Insulation class: insulation class I (protective earthing)
- Impact resistance: IK06
- Protection symbol: D if used in an environment with non-conductive dust loads with corresponding accessories
- Temperature range (operation): -25...+35°C
- Supplement: corresponds to IFS (International Featured Standards) requirements for safety and quality in the food industry, reducing of maximum allowable ambient temperature of 5°C with ceiling mounting, LABS conformity tested according to VDMA 24364:2018-05
- Standard: EN 60598-2-22
- Certification, designation: CE, ENEC, VDE, UKCA

## Material, Colour

- Licross® LED insert: sheet steel, galvanised, coil coated, white
- Colour specification: white
- Cover: cover of PMMA

## Mounting

- Mounting method, mounting location: slip-in mounting, in the Licross® trunking rail
- Arrangement: single/continuous arrangement
- Supplement: only suitable for use in indoor areas

## Electrical connection

- Connection: plug, 6-pole, with phase selection
- Nominal voltage: 220...240V, 0/50...60Hz, AC/DC

## Dimensions, Weight

- Length: 1500mm
- Width: 120mm
- Height: 123mm
- Weight: 3.1kg

## Service life

- Rated service life: 100000h (L95/B50) at AT = 25°C, 100000h (L90/B50) at AT = ta max

**Order No.:** 51TD16DN6EXMD | **GTIN (EAN):** 4069025003300

**Dimensions:** Lic11Pe,wd,14180lm865,DA2,IP54,L1500,wh



It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at [www.siteco.de](http://www.siteco.de))

Tolerances related to thermal, electrical and photometric data according to IEC 62722

Issued 06.06.2025 - Modifications and errors subject to change - Ensure that you always use the latest version -