

Order No.: 5LZ904315 | **GTIN (EAN):** 4058352559925

Product description: SCon,controller,locCtrl



SITECO Connectcontroller, master, local control - self-sufficient standalone sensors, dimmable, installation type: recessed, installation location: in the ceiling, of plastic, protection rating (complete): IP20, insulation class (complete): insulation class II (safety insulation), certification: CE, voltage: 220..240V, voltage type: AC, 1 x push button input, 1 x service push button, 1 x DALI, packaging unit: 1 piece

IP 20  

Wt. (kg):	0.1
GTIN (EAN):	4058352559925

Order No.: 5LZ904315 | **GTIN (EAN):** 4058352559925

Detailed technical description: SCon,controller,locCtrl

Key data

- System family: SITECO Connect 32
- Product type: lighting management components
- Product name: SITECO Connect
- Order No.: 5LZ904315

Lighting technology | Lamps | Control gear

Component 1

Operating device:

- Control: DALI, dimmable

Certificates, Standards

- Protection rating: IP20
- Insulation class: insulation class II (safety insulation)
- Temperature range (operation): - 20..+60°C
- Certification, designation: CE

Material, Colour

- housing: plastic, pure white (RAL 9010)
- Colour specification: pure white (RAL 9010)

Mounting

- Mounting method, mounting location: recessed, in the ceiling
- Supplement: only suitable for use in indoor areas

Electrical connection

- Connection: terminal, 2-pole, max. 1.5mm²
- Nominal voltage: 220..240V, 50/60Hz, AC

Dimensions, Weight

- Length: 108mm
- Width: 30mm
- Height: 21mm
- Weight: 0.1kg

Inputs

1x push button input

- Connection: screw terminal, 2-pole, max. 1.5mm²
- Feature: zero-potential

1x service push button

- Option: reset

Outputs

1x DALI

- Connection: screw terminal, 2-pole, max. 1.5mm²
- System current: DALI current 96mA
- Feature: DALI, master function, broadcast addressing, max. 32 DALI ECGs