


**Order No.:** 5EA3CLS02 | **GTIN (EAN):** 4069025570703

**Product description:** SConWi,SmartPlugLoRaWAN




SITECO Connect WirelessSmart Plug LoRaWAN, luminaire controller, radio, communication: LoRaWAN, D4i type A, control: remote setup and operation, sensor technology: daylight sensor, Smart Interface below and above, The LoRaWAN keys are transmitted as a file, installation type: screw fastening, installation location: to the luminaire, Smart Interface above: Zhaga, Smart Interface below: Zhaga, of PBT, voltage: 24V, voltage type: DC, protection rating (complete): IP66, certification: CE, packaging unit: set of 48

IP 66 CE

Wt. (kg): 0.1  
GTIN (EAN): 4069025570703

Order No.: 5EA3CLS02 | GTIN (EAN): 4069025570703

Detailed technical description: SConWi,SmartPlugLoRaWAN



#### Key data

- System family: SITECO Connect
- Product type: luminaire controller
- Product name: SITECO Connect Wireless
- Order No.: 5EA3CLS02

#### Lighting technology | Lamps | Control gear

#### Component 1

#### Operating device:

- Control: D4i, Smart Interface below and above, The LoRaWAN keys are transmitted as a file

#### Certificates, Standards

- Protection rating: IP66
- Temperature range (operation): -40..+70°C
- Standard: according to Zhaga book 18
- Certification, designation: CE

#### Material, Colour

- housing: PBT, transparent, colour-backed, transparent

#### Mounting

- Mounting method, mounting location: screw fastening, to the luminaire

#### Electrical connection

- Nominal voltage: 24V, DC

#### Dimensions, Weight

- Diameter: 80mm
- Height: 45mm
- Weight: 0.1kg