

Order No.: 51SE61DA2EC2C | GTIN (EAN): 4069025447685

Product description: Spot21,spot,2200lm935,DA2ML,70,sr



Spot 21, directional spotlight, light control with lens, of PMMA, beam angle: spotlight, LED rated luminous flux: 2.200lm, light colour: 935, with 3-phase adapter, mains connection: 220..240V, AC, 50/60Hz, of aluminium, metallic grey (RAL 9006), length: 251mm, diameter: 70mm, decorative ring, of PC, metallic grey (RAL 9006), protection rating (complete): IP20, insulation class (complete): insulation class II (safety insulation), certification: CE, impact resistance: IK02, permissible ambient temperature for indoor applications: -20..+25°C, packaging unit: 1 piece

IP 20  

Lamps:	LED
Wt. (kg):	0.5
GTIN (EAN):	4069025447685



Order No.: 51SE61DA2EC2C | **GTIN (EAN):** 4069025447685

Detailed technical description: Spot21,spot,2200lm935,DA2ML,70,sr



Key data

- Product type: directional spotlight
- Product name: Spot 21
- Order No.: 51SE61DA2EC2C

Lighting technology | Lamps | Control gear

Component 1

Lighting technology:

- Light control: lens of PMMA
- Beam angle: spotlight
- Symmetry: symmetric

Lamps:

- Lamps: with LED
- Rated luminous flux: 2200lm
- Luminous efficacy: 141lm/W
- Colour temperature: 3500K
- Colour rendering index: CRI > 90
- Light colour: 935
- SDCM (Standard Deviation of Colour Matching): MacAdam ≤ 2 SDCM (initial)
- Rated input power: 15.5W
- Supplement: luminous flux adjustable on luminaire in 12 steps (850/.../3630lm), connected load according to luminous flux setting (6/.../28W)

Operating device:

- Control: DALI 2, Multilumen

Certificates, Standards

- Protection rating: IP20
- Insulation class: insulation class II (safety insulation)
- Impact resistance: IK02
- Temperature range (operation): -20..+25°C
- Certification, designation: CE

Material, Colour

- decorative ring: PC, metallic grey (RAL 9006)

Mounting

- Mounting method, mounting location: slip-in mounting, in a 3-phase track

Electrical connection

- Connection: 3-phase adapter
- Nominal voltage: 220..240V, 50/60Hz, AC

Dimensions, Weight

- Length: 251mm
- Diameter: 70mm
- Weight: 0.5kg

Service life

- Rated service life: 50000h (L90/B10) at AT = 25°C

Order No.: 51SE61DA2EC2C | GTIN (EAN): 4069025447685

Dimensions: Spot21,spot,2200lm935,DA2ML,70,sr

