

Order No.: 56TL3M02 | **GTIN (EAN):** 4069025886996

Product description: Lic,multiadapter,sh.steel,bk,IP20/40

Licross, rail insert, adapter,with plug, 5-pole, with phase selection, mains connection: 230V, AC, 50/60Hz, terminal,5-pole, max. 2.5mm², multi adapter, of sheet steel, coil coated, matt jet black (RAL 9005), for IP20/IP40 protection rating, length: 500mm, width: 64mm, height: 68mm, multifunctional insert, protection rating (complete): IP20, insulation class (complete): insulation class I (protective earthing), certification: CE, UKCA, packaging unit: 1 piece

IP 20  

Wt. (kg):	0.6
GTIN (EAN):	4069025886996

Order No.: 56TL3M02 | **GTIN (EAN):** 4069025886996

Detailed technical description: Lic,multiadapter,sh.steel,bk,IP20/40

Key data

- System family: Licross
- Product type: rail insert
- Product name: Licross
- Order No.: 56TL3M02

Lighting technology | Lamps | Control gear

Component 1

Lamps:

- Supplement: internal wiring halogen-free, for trunking rail, 7..14-core, max. 0.5A

Certificates, Standards

- Protection rating: IP20
- Insulation class: insulation class I (protective earthing)
- Certification, designation: CE, UKCA

Material, Colour

- multi adapter: sheet steel, coil coated, matt jet black (RAL 9005), for IP20/IP40 protection rating

Mounting

- Supplement: only suitable for use in indoor areas

Electrical connection

- Connection: plug, 5-pole, with phase selection
- Nominal voltage: 230V, 50/60Hz, AC

Dimensions, Weight

- Length: 500mm
- Width: 64mm
- Height: 68mm
- Weight: 0.6kg