


Order No.: 59MX2AW000SA | **GTIN (EAN):** 4058352608814

Product description: Sil21,controller,wirel




Silica® 21, controller, master,local controlinstallation type: slip-in mounting,
installation location: to the luminaire, of extruded aluminium section,
protection rating (complete): IP20, insulation class (complete): insulation class
I (protective earthing), certification: CE, packaging unit: 1 piece

IP 20  

Wt. (kg): 999.0
GTIN (EAN): 4058352608814

Order No.: 59MX2AW000SA | GTIN (EAN): 4058352608814

Detailed technical description: Sil21,controller,wirel



Key data

- System family: SITECO Connect Wireless
- Product type: control unit
- Product name: Silica® 21
- Order No.: 59MX2AW000SA

Lighting technology | Lamps | Control gear

Component 1

Operating device:

- Control: Bluetooth® mesh 4.2

Certificates, Standards

- Protection rating: IP20
- Insulation class: insulation class I (protective earthing)
- Temperature range (operation): 0..+40°C
- Certification, designation: CE

Material, Colour

- housing: extruded aluminium section, anodised, metallic grey (RAL 9006)
- Colour specification: metallic grey (RAL 9006)

Mounting

- Mounting method, mounting location: slip-in mounting, to the luminaire
- Supplement: for surface-mounted luminaires, for pendant luminaires

Dimensions, Weight

- Width: 53mm
- Height: 53mm
- Weight: 999.0kg