

Photometric test report

Family
Lunis 41

Order number: 51DR107DGBA
EAN: 4058352509920

LP number
59234_1

serial
documentation
07.12.2021



Version diffuse cover, extremely wide distribution,
adjustable color temperature: 3000 K | 4000 K

Lamps LED 3000 K | CRI ≥ 80

Controlgear ECG

Setting individual position: colour temperature 3000K

Rated values Net luminous flux = 1250 lm
Power consumption = 15.0 W
Luminous efficacy = 83.3 lm/W


siteco

Luminous intensity in cd/klm

C180-0

C270-90

Imax: 369 cd/klm



Classifications

DIN 5040 A 4 0
CIE N1=49 N2=80 N3=96
N4=100 N5=100

Luminaire light output ratios

η_{LB} 100.0%
 ϕ_u 100.0%
 ϕ_o 0.0%

Measurement conditions

DIN EN 13032 and DIN 5032

Photometric test report

Family Lunis 41	Order number: 51DR107DGBA EAN: 4058352509920	LP number 59234_1
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C- planes	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm							Luminous flux in lm/klm	
0°	368.6	368.6	368.6	368.6	368.6	368.6	368.6	2.2	2.2
5°	367.2	366.8	366.3	365.8	365.5	365.3	365.0	17.5	19.7
10°	362.1	361.4	360.8	360.1	359.5	358.9	358.3	34.3	54.0
15°	354.2	353.1	351.9	350.8	350.1	349.3	348.6	49.8	103.8
20°	342.9	341.5	340.1	338.8	337.8	336.9	336.0	63.6	167.3
25°	327.9	326.3	324.6	323.0	321.8	320.6	319.4	74.9	242.3
30°	310.7	308.8	306.8	304.8	303.5	302.2	300.8	83.7	325.9
35°	290.5	288.3	286.2	284.0	282.5	281.0	279.5	89.4	415.4
40°	267.0	264.6	262.3	260.0	258.4	256.8	255.2	91.8	507.2
45°	242.2	239.7	237.3	234.8	233.0	231.3	229.5	91.2	598.4
50°	215.7	213.2	210.6	208.1	206.2	204.3	202.4	87.6	686.0
55°	186.3	184.1	181.9	179.7	177.4	175.1	172.8	80.7	766.6
60°	157.1	154.5	151.9	149.2	146.6	144.0	141.4	70.8	837.5
65°	128.1	125.1	122.0	118.9	116.8	114.6	112.5	59.4	896.9
70°	96.9	93.9	90.9	87.9	85.9	83.8	81.7	45.6	942.5
75°	66.8	64.2	61.7	59.2	57.0	54.7	52.5	31.5	974.0
80°	40.0	39.6	39.2	38.8	35.1	31.4	27.8	19.6	993.6
85°	16.1	14.5	12.9	11.3	10.3	9.3	8.3	6.4	1000.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0

Photometric test report

Family Lunis 41			Order number: 51DR107DGBA EAN: 4058352509920							LP number 59234_1	
UGR-Table			Standard room							siteco	
Reflection factor of ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Reflection factor of walls		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reflection factor of floor		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		View crosswise (C0)					View endwise (C90)				
x	y										
2H	2H	24.5	26.2	24.9	26.5	26.8	24.2	25.9	24.5	26.2	26.5
	3H	26.1	27.6	26.5	28.0	28.3	25.6	27.1	26.0	27.4	27.8
	4H	26.8	28.2	27.1	28.5	28.9	26.1	27.5	26.5	27.9	28.2
	6H	27.2	28.5	27.6	28.9	29.3	26.4	27.7	26.8	28.1	28.5
	8H	27.4	28.6	27.8	29.0	29.4	26.5	27.7	26.9	28.1	28.5
	12H	27.5	28.7	28.0	29.1	29.5	26.5	27.7	27.0	28.1	28.5
4H	2H	25.2	26.6	25.6	27.0	27.4	25.0	26.4	25.3	26.7	27.1
	3H	27.0	28.2	27.4	28.6	29.0	26.5	27.7	27.0	28.1	28.5
	4H	27.7	28.8	28.1	29.2	29.6	27.1	28.2	27.6	28.6	29.1
	6H	28.3	29.3	28.8	29.7	30.1	27.6	28.5	28.0	28.9	29.4
	8H	28.5	29.4	29.0	29.8	30.3	27.7	28.5	28.1	29.0	29.5
	12H	28.7	29.4	29.2	29.9	30.4	27.7	28.5	28.2	29.0	29.5
8H	4H	28.0	28.9	28.5	29.3	29.8	27.5	28.3	27.9	28.8	29.2
	6H	28.7	29.4	29.2	29.9	30.4	28.0	28.8	28.5	29.2	29.7
	8H	29.0	29.6	29.5	30.1	30.6	28.2	28.8	28.7	29.3	29.8
	12H	29.2	29.7	29.7	30.2	30.7	28.3	28.8	28.8	29.3	29.9
12H	4H	28.0	28.8	28.5	29.3	29.7	27.5	28.3	28.0	28.8	29.2
	6H	28.8	29.4	29.3	29.9	30.4	28.1	28.8	28.6	29.2	29.8
	8H	29.1	29.6	29.6	30.1	30.7	28.3	28.9	28.8	29.4	29.9

Luminance table		Max. for $\gamma \geq 65^\circ$		Photometric dimensions in mm:		D = 125	
C-planes	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°
γ	Luminance in cd/m²						
45°	34890.4	34535.7	34181.2	33826.4	33570.4	33314.6	33058.6
50°	34182.6	33780.4	33378.4	32976.2	32674.3	32372.8	32071.0
55°	33087.8	32695.9	32303.6	31911.5	31501.5	31091.2	30681.2
60°	32000.5	31467.8	30935.4	30402.7	29870.2	29337.5	28805.0
65°	30886.1	30139.9	29393.5	28647.3	28139.5	27631.7	27123.8
70°	28844.7	27960.2	27075.7	26191.5	25571.4	24951.6	24331.9
75°	26280.3	25281.1	24282.6	23283.8	22414.5	21545.9	20676.5
80°	23448.7	23210.5	22971.8	22733.6	20589.7	18446.3	16302.3
85°	18776.4	16936.8	15098.5	13258.9	12072.7	10886.5	9699.1

Photometric test report

Family
Lunis 41

Order number: 51DR107DGBA
EAN: 4058352509920

LP number
59234_1

Luminance values in cd/m²

γ 65°

γ 70°

γ 75°

γ 80°

γ 85°

siteco

