

Photometric test report

Family
Monsun® 12

Order number: 51FP109P460H
EAN: 4058352376300

LP number
58939_6



Version prismatic diffuser, opal, PMMA, wide distribution
Lamps LED 4000 K | CRI ≥ 80
Controlgear ECG CLOi
Rated values Net luminous flux = 6100 lm
Power consumption = 34.0 W
Luminous efficacy = 179.4 lm/W

serial
documentation
09.07.2020


siteco

Luminous intensity in cd/klm

C180-0

C270-90

Imax: 340 cd/klm



Classifications

DIN 5040 A 4 1
CIE N1=47 N2=77 N3=93
N4=94 N5=100

Luminaire light output ratios

η_{LB} 100.0%
 ϕ_u 94.2%
 ϕ_o 5.8%

Measurement conditions

DIN EN 13032 and DIN 5032

Photometric test report

Family Monsun® 12	Order number: 51FP109P460H EAN: 4058352376300	LP number 58939_6
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C- planes	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm							Luminous flux in lm/klm	
0°	340.1	340.1	340.1	340.1	340.1	340.1	340.1	2.0	2.0
5°	339.4	338.3	336.5	337.9	339.5	339.4	339.8	16.2	18.2
10°	333.5	333.0	331.2	332.8	334.6	334.7	335.0	31.7	49.9
15°	324.2	324.2	322.5	324.2	326.1	326.4	326.9	46.1	96.0
20°	311.0	311.6	310.1	311.9	314.1	314.7	315.3	58.6	154.6
25°	294.4	295.4	294.1	296.0	298.4	299.4	300.2	68.7	223.4
30°	275.2	276.6	275.1	276.8	279.4	280.7	281.6	76.1	299.5
35°	253.9	255.2	253.8	254.9	257.1	258.4	259.7	80.5	380.0
40°	231.8	232.9	231.3	231.1	232.5	233.8	235.1	81.9	461.9
45°	209.4	209.9	207.8	205.9	206.1	206.6	208.2	80.4	542.4
50°	187.2	187.1	184.8	181.3	179.3	178.3	179.7	76.6	619.0
55°	165.5	164.8	162.1	157.0	153.1	150.2	150.9	70.7	689.7
60°	143.9	142.9	139.5	133.7	127.9	123.2	122.7	63.3	753.0
65°	123.6	122.5	117.8	111.0	104.2	97.9	96.0	54.9	808.0
70°	104.7	103.3	97.1	89.4	81.7	74.3	71.0	45.8	853.8
75°	86.1	84.4	77.8	69.2	60.2	52.2	47.8	36.3	890.0
80°	68.0	66.1	60.2	50.5	40.7	32.1	26.9	26.7	916.7
85°	51.8	50.0	44.6	35.3	24.7	15.7	10.1	18.3	935.0
90°	40.8	39.2	34.4	26.0	15.9	6.9	1.8	13.1	948.2
95°	34.8	33.5	29.7	22.7	13.6	5.1	1.6	11.2	959.3
100°	29.9	28.8	25.4	19.2	11.3	3.7	1.4	9.4	968.7
105°	25.7	24.7	21.4	16.1	8.8	2.4	1.2	7.7	976.4
110°	22.1	20.9	18.0	13.0	6.6	1.4	1.1	6.1	982.5
115°	19.0	17.8	15.0	10.4	4.7	1.2	1.1	4.9	987.4
120°	16.0	14.8	12.2	7.9	3.1	1.2	1.0	3.8	991.2
125°	13.0	11.9	9.4	5.6	1.7	1.1	0.9	2.7	993.9
130°	10.1	9.1	6.9	3.7	1.4	1.1	1.0	1.9	995.9
135°	7.3	6.5	4.6	2.1	1.4	1.1	1.1	1.3	997.1
140°	4.8	4.1	2.7	1.7	1.4	1.1	1.1	0.8	998.0
145°	2.6	2.3	1.9	1.7	1.4	1.2	1.2	0.5	998.5
150°	2.0	2.0	1.9	1.6	1.3	1.3	1.3	0.4	998.9
155°	1.9	1.9	1.7	1.6	1.4	1.4	1.4	0.4	999.3
160°	1.7	1.7	1.6	1.4	1.4	1.4	1.4	0.3	999.6
165°	1.4	1.4	1.4	1.4	1.4	1.4	1.4	0.2	999.8
170°	1.3	1.4	1.4	1.4	1.4	1.4	1.4	0.1	999.9
175°	1.4	1.4	1.4	1.4	1.4	1.4	1.4	0.1	1000.0
180°	1.4	1.4	1.4	1.4	1.4	1.4	1.4	0.0	1000.0

Photometric test report

Family Monsun® 12	Order number: 51FP109P460H EAN: 4058352376300	LP number 58939_6
----------------------	--	----------------------

UGR-Table		Standard room							siTeco		
Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		View crosswise (C0)					View endwise (C90)				
x	y										
2H	2H	20.1	21.8	20.5	22.1	22.4	20.1	21.8	20.4	22.1	22.4
	3H	21.8	23.4	22.2	23.7	24.1	21.5	23.0	21.8	23.3	23.7
	4H	22.7	24.1	23.1	24.5	24.8	22.0	23.4	22.4	23.8	24.2
	6H	23.4	24.8	23.8	25.1	25.5	22.4	23.7	22.8	24.1	24.5
	8H	23.8	25.0	24.2	25.4	25.8	22.5	23.8	22.9	24.1	24.5
	12H	24.1	25.3	24.5	25.7	26.1	22.5	23.7	23.0	24.1	24.6
4H	2H	20.8	22.3	21.2	22.6	23.0	20.8	22.2	21.2	22.6	23.0
	3H	22.7	24.0	23.2	24.4	24.8	22.4	23.6	22.8	24.0	24.4
	4H	23.7	24.8	24.1	25.2	25.7	23.0	24.1	23.4	24.5	25.0
	6H	24.6	25.6	25.1	26.0	26.5	23.5	24.5	23.9	24.9	25.4
	8H	25.0	25.9	25.5	26.4	26.9	23.6	24.6	24.1	25.0	25.5
	12H	25.4	26.3	25.9	26.7	27.2	23.7	24.6	24.2	25.0	25.5
8H	4H	24.0	24.9	24.5	25.4	25.9	23.4	24.3	23.9	24.8	25.2
	6H	25.1	25.9	25.6	26.3	26.8	24.0	24.8	24.5	25.3	25.8
	8H	25.6	26.3	26.1	26.8	27.3	24.2	24.9	24.7	25.4	25.9
	12H	26.2	26.8	26.7	27.3	27.8	24.4	25.0	24.9	25.5	26.0
12H	4H	24.1	24.9	24.5	25.3	25.8	23.5	24.3	24.0	24.8	25.3
	6H	25.2	25.9	25.7	26.3	26.9	24.2	24.9	24.7	25.3	25.8
	8H	25.8	26.4	26.3	26.9	27.4	24.5	25.0	25.0	25.5	26.1

Luminance table		Max. for $\gamma \geq 65^\circ$		Photometric dimensions in mm:		L = 1590 B = 87		H(C0) = 21 H(C90) = 21		H(C180) = 21 H(C270) = 21	
C-planes	γ	0°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°			
		Luminance in cd/m²									
	45°	10518.2	10583.4	10660.8	10883.7	11353.5	11982.2	12813.5			
	50°	9975.8	10012.7	10087.6	10241.5	10628.8	11225.9	12136.7			
	55°	9459.4	9470.5	9528.5	9603.5	9902.9	10424.7	11384.5			
	60°	8949.2	8941.6	8957.2	8985.6	9182.9	9613.9	10582.0			
	65°	8500.5	8480.1	8408.3	8355.0	8472.3	8796.6	9741.5			
	70°	8115.3	8069.5	7860.1	7711.6	7725.3	7935.9	8838.5			
	75°	7713.7	7640.9	7347.7	7049.7	6874.8	6945.7	7765.0			
	80°	7288.0	7167.0	6873.3	6343.4	5901.7	5705.3	6350.0			
	85°	6977.4	6829.7	6510.4	5846.1	4969.3	4257.9	4434.7			

Photometric test report

Family
Monsun® 12

Order number: 51FP109P460H
EAN: 4058352376300

LP number
58939_6

Luminance values in cd/m²

γ 65°

γ 70°

γ 75°

γ 80°

γ 85°

siteco

