


# Photometric test report

<b>Family</b> <b>Licross® Spot 31</b>	<b>Order number: 51SL12DA43B</b> <b>EAN: 4058352863510</b>	<b>LP number</b> <b>59381_20</b>
	<b>Version</b> reflector, cover, polycarbonate, narrow distribution, luminaire housing, aluminium, white	<b>serial documentation</b> <b>12.07.2023</b>
	<b>Lamps</b> LED 4000 K   CRI ≥ 90	
	<b>Controlgear</b> ECG-DALI	
	<b>Setting</b> factory setting: DIP-Step=7	
<b>Rated values</b>	Net luminous flux = 3650 lm Power consumption = 28.6 W Luminous efficacy = 127.6 lm/W	

**Luminous intensity in cd/klm** C180-0 **Imax: 4501 cd/klm**



Classifications	
DIN 5040	A 7 0
CIE	N1=93 N2=97 N3=99 N4=100 N5=100

Luminaire light output ratios	
$\eta_{LB}$	100.0%
$\phi_u$	100.0%
$\phi_o$	0.0%

**Measurement conditions**  
 DIN EN 13032 and DIN 5032

## Photometric test report

Family <b>Licross® Spot 31</b>	Order number: <b>51SL12DA43B</b> EAN: <b>4058352863510</b>	LP number <b>59381_20</b>
<b>Table of values for luminous intensities</b>		<b>Maximum luminous intensity</b>
		<b>siteco</b>

C-planes	0°	Phi-zone	Total Phi-zone
$\gamma$	Luminous intensity in cd/klm		Luminous flux in lm/klm
0°	4500.5	1.1	1.1
1°	4480.3	8.6	9.7
2°	4437.5	17.0	26.6
3°	4362.0	25.0	51.7
4°	4236.1	32.4	84.1
5°	4010.1	38.3	122.4
6°	3672.5	42.1	164.5
7°	3309.8	44.2	208.7
8°	2898.6	44.2	253.0
9°	2482.5	42.6	295.6
10°	2122.6	40.4	336.0
11°	1782.7	37.3	373.3
12°	1538.7	35.1	408.4
13°	1327.4	32.7	441.1
14°	1130.4	30.0	471.1
15°	985.0	28.0	499.1
16°	859.9	26.0	525.0
17°	761.9	24.4	549.5
18°	683.9	23.2	572.6
19°	616.9	22.0	594.7
20°	570.3	21.4	616.1
21°	532.3	20.9	637.0
22°	498.2	20.5	657.4
23°	472.4	20.2	677.7
24°	451.2	20.1	697.8
25°	433.6	20.1	717.9
26°	418.4	20.1	738.0
27°	405.2	20.2	758.2
28°	393.9	20.3	778.5
29°	380.9	20.3	798.7
30°	356.4	19.5	818.3
31°	326.4	18.4	836.7
32°	294.9	17.1	853.8
33°	256.7	15.3	869.2
34°	220.2	13.5	882.7
35°	180.4	11.3	894.0
36°	146.1	9.4	903.4
37°	111.1	7.3	910.8
38°	79.1	5.3	916.1
39°	56.1	3.9	920.0
40°	40.9	2.9	922.8
41°	37.1	2.7	925.5
42°	35.5	2.6	928.1
43°	33.6	2.5	930.6
44°	33.1	2.5	933.2
45°	33.1	2.6	935.7
46°	32.9	2.6	938.3

C-planes	0°	Phi-zone	Total Phi-zone
$\gamma$	Luminous intensity in cd/klm		Luminous flux in lm/klm
47°	33.1	2.7	941.0
48°	33.6	2.7	943.7
49°	34.5	2.9	946.6
50°	35.6	3.0	949.6
51°	36.2	3.1	952.6
52°	35.7	3.1	955.7
53°	33.7	2.9	958.7
54°	30.9	2.7	961.4
55°	27.6	2.5	963.9
56°	23.6	2.1	966.1
57°	21.0	1.9	968.0
58°	19.1	1.8	969.8
59°	17.3	1.6	971.4
60°	16.3	1.5	972.9
61°	15.8	1.5	974.5
62°	15.5	1.5	976.0
63°	15.1	1.5	977.4
64°	14.4	1.4	978.9
65°	14.1	1.4	980.3
66°	13.7	1.4	981.6
67°	13.0	1.3	982.9
68°	12.9	1.3	984.3
69°	12.5	1.3	985.5
70°	12.0	1.2	986.8
71°	11.4	1.2	988.0
72°	11.1	1.2	989.1
73°	10.6	1.1	990.2
74°	10.1	1.1	991.3
75°	9.5	1.0	992.3
76°	8.7	0.9	993.2
77°	7.7	0.8	994.0
78°	6.8	0.7	994.8
79°	6.5	0.7	995.5
80°	6.1	0.7	996.1
81°	5.4	0.6	996.7
82°	5.2	0.6	997.3
83°	4.8	0.5	997.8
84°	4.1	0.5	998.2
85°	3.8	0.4	998.7
86°	3.1	0.3	999.0
87°	3.1	0.3	999.3
88°	2.5	0.3	999.6
89°	2.2	0.2	999.9
90°	2.5	0.3	1000.1

## Photometric test report

Family <b>Licross® Spot 31</b>	Order number: <b>51SL12DA43B</b> EAN: <b>4058352863510</b>	LP number <b>59381_20</b>
-----------------------------------	---	------------------------------

<b>UGR-Table</b>	<b>Standard room</b>	<b>siteco</b>
------------------	----------------------	---------------

Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions	View crosswise (C0)					View endwise (C90)					
x	y										
2H	2H	21.0	22.0	21.4	22.4	22.7	21.0	22.0	21.4	22.4	22.7
	3H	21.5	22.5	21.9	22.8	23.2	21.5	22.5	21.9	22.8	23.2
	4H	21.9	22.8	22.3	23.1	23.5	21.9	22.8	22.3	23.1	23.5
	6H	22.2	23.0	22.6	23.4	23.7	22.2	23.0	22.6	23.4	23.7
	8H	22.5	23.1	22.9	23.5	23.9	22.5	23.1	22.9	23.5	23.9
	12H	22.6	23.2	23.0	23.6	24.0	22.6	23.2	23.0	23.6	24.0
4H	2H	21.1	21.9	21.5	22.3	22.7	21.1	21.9	21.5	22.3	22.7
	3H	21.9	22.6	22.3	22.9	23.4	21.9	22.6	22.3	22.9	23.4
	4H	22.4	23.0	22.8	23.4	23.9	22.4	23.0	22.8	23.4	23.9
	6H	22.8	23.3	23.2	23.8	24.2	22.8	23.3	23.2	23.8	24.2
	8H	23.0	23.5	23.5	24.0	24.4	23.0	23.5	23.5	24.0	24.4
	12H	23.2	23.7	23.7	24.1	24.6	23.2	23.7	23.7	24.1	24.6
8H	4H	22.5	23.0	23.0	23.5	23.9	22.5	23.0	23.0	23.5	23.9
	6H	23.1	23.5	23.6	24.0	24.5	23.1	23.5	23.6	24.0	24.5
	8H	23.4	23.8	23.9	24.2	24.8	23.4	23.8	23.9	24.2	24.8
	12H	23.7	24.0	24.2	24.5	25.1	23.7	24.0	24.2	24.5	25.1
12H	4H	22.5	22.9	23.0	23.4	23.9	22.5	22.9	23.0	23.4	23.9
	6H	23.1	23.5	23.6	24.0	24.5	23.1	23.5	23.6	24.0	24.5
	8H	23.5	23.8	24.0	24.3	24.8	23.5	23.8	24.0	24.3	24.8

<b>Luminance table</b>	<b>Max. for <math>\gamma \geq 65^\circ</math></b>	<b>Photometric dimensions in mm: D = 79</b>
------------------------	---	---

<b>C-planes</b>	<b>0°</b>
$\gamma$	<b>Luminance in cd/m²</b>
45°	34836.1
50°	41285.2
55°	35887.5
60°	24300.7
65°	24845.7
70°	26074.1
75°	27292.0
80°	25965.3
85°	32816.9

**Photometric test report**


**Family**  
**Licross® Spot 31**

**Order number: 51SL12DA43B**  
**EAN: 4058352863510**

**LP number**  
**59381\_20**

**Luminance values in cd/m<sup>2</sup>**

$\gamma$  65°  
   $\gamma$  70°  
   $\gamma$  75°  
   $\gamma$  80°  
   $\gamma$  85°



### Photometric test report

Family <b>Licross® Spot 31</b>	Order number: <b>51SL12DA43B</b> EAN: <b>4058352863510</b>	LP number <b>59381_20</b>
-----------------------------------	---	------------------------------

<b>Multilumen Table</b>	environmental temperature: 25°C	<b>sITeco</b>
-------------------------	---------------------------------	---------------

DIP-Step	Switch Setting			Luminous flux [lm]	Power consumption [W]
	1	2	3		
7	ON	ON	ON	3650	28.6
6	OFF	ON	ON	3430	26.5
5	ON	OFF	ON	3190	24.4
4	OFF	OFF	ON	2960	22.4
3	ON	ON	OFF	2710	20.4
2	OFF	ON	OFF	2440	18.4
1	ON	OFF	OFF	2190	16.3
0	OFF	OFF	OFF	1840	14.4