

Photometric test report

Family
Licross® 11 Recessed

Order number: 51TE12DN4AXG3C
EAN: 4058352934746

LP number
58637_189



Version cover frosted, wide distribution, high visual comfort
Lamps LED 4000 K | CRI ≥ 80
Controlgear ECG-DALI
Setting AC-mode
Rated values Net luminous flux = 10240 lm
Power consumption = 60.5 W
Luminous efficacy = 169.2 lm/W

serial
documentation
29.09.2023


siteco

Luminous intensity in cd/klm

C180-0

C270-90

Imax: 498 cd/klm



Classifications

DIN 5040 A 5 0
CIE N1=67 N2=92 N3=99
N4=100 N5=100

Luminaire light output ratios

η_{LB} 100.0%
 ϕ_u 100.0%
 ϕ_o 0.0%

Measurement conditions

DIN EN 13032 and DIN 5032

Photometric test report

Family Licross® 11 Recessed	Order number: 51TE12DN4AXG3C EAN: 4058352934746	LP number 58637_189
Table of values for luminous intensities		Maximum luminous intensity



C-planes	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm							Luminous flux in lm/klm	
0°	482.3	482.3	482.3	482.3	482.3	482.3	482.3	2.9	2.9
5°	485.4	482.8	478.2	477.5	477.4	475.9	475.7	22.9	25.8
10°	492.7	488.2	477.9	471.3	467.6	465.9	466.0	45.2	71.0
15°	493.2	486.1	471.9	467.9	471.0	473.7	476.3	67.5	138.5
20°	482.5	473.5	462.5	471.9	487.1	492.8	494.9	89.9	228.4
25°	456.4	447.1	449.2	479.4	497.6	491.1	485.8	109.5	337.8
30°	414.9	406.8	427.0	475.1	479.0	447.1	431.1	121.4	459.2
35°	364.2	358.0	387.7	436.7	420.7	368.9	346.8	122.0	581.2
40°	300.5	296.3	322.5	357.9	336.0	284.8	262.9	110.4	691.6
45°	229.2	226.3	238.5	259.8	247.2	211.8	193.4	90.1	781.7
50°	162.3	159.3	161.6	173.6	174.5	155.2	138.5	68.2	849.9
55°	112.5	108.0	105.1	112.3	121.6	110.9	97.2	49.6	899.5
60°	78.7	73.1	68.3	73.1	83.7	77.4	68.5	35.5	935.0
65°	56.0	50.2	45.0	48.4	56.8	54.5	49.6	25.5	960.5
70°	39.5	34.5	29.5	32.1	37.8	38.5	36.6	18.1	978.6
75°	26.0	22.0	18.4	20.2	23.9	25.9	25.8	12.0	990.6
80°	14.9	12.2	9.9	10.8	13.0	14.8	15.3	6.8	997.4
85°	5.4	4.3	3.6	4.0	4.7	5.6	5.8	2.5	1000.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0

Photometric test report

Family Licross® 11 Recessed	Order number: 51TE12DN4AXG3C EAN: 4058352934746	LP number 58637_189
--------------------------------	--	------------------------

UGR-Table		Standard room									siteco	
Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3		
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3		
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2		
Room dimensions		View crosswise (C0)					View endwise (C90)					
x	y											
2H	2H	22.7	24.2	23.1	24.5	24.8	22.8	24.3	23.2	24.6	24.9	
	3H	23.2	24.6	23.6	24.9	25.2	23.4	24.7	23.7	25.0	25.4	
	4H	23.5	24.7	23.8	25.0	25.4	23.6	24.8	24.0	25.2	25.5	
	6H	23.6	24.7	24.0	25.1	25.5	23.8	24.9	24.2	25.3	25.7	
	8H	23.7	24.7	24.1	25.1	25.5	23.9	24.9	24.3	25.3	25.7	
	12H	23.7	24.7	24.2	25.1	25.5	23.9	24.9	24.4	25.3	25.7	
4H	2H	22.9	24.2	23.3	24.5	24.9	23.0	24.3	23.4	24.6	25.0	
	3H	23.5	24.6	24.0	25.0	25.4	23.7	24.8	24.2	25.1	25.6	
	4H	23.8	24.7	24.3	25.1	25.6	24.1	25.0	24.5	25.4	25.8	
	6H	24.0	24.8	24.5	25.3	25.7	24.3	25.1	24.8	25.6	26.0	
	8H	24.1	24.8	24.6	25.3	25.8	24.4	25.2	24.9	25.6	26.1	
	12H	24.2	24.8	24.7	25.3	25.8	24.5	25.1	25.0	25.6	26.1	
8H	4H	23.9	24.6	24.4	25.0	25.5	24.1	24.8	24.6	25.3	25.8	
	6H	24.1	24.7	24.6	25.2	25.7	24.5	25.0	25.0	25.5	26.0	
	8H	24.2	24.8	24.7	25.2	25.8	24.6	25.1	25.1	25.6	26.1	
	12H	24.3	24.7	24.8	25.2	25.8	24.7	25.1	25.2	25.6	26.2	
12H	4H	23.9	24.5	24.4	25.0	25.5	24.1	24.7	24.6	25.2	25.7	
	6H	24.2	24.7	24.7	25.1	25.7	24.5	25.0	25.0	25.5	26.0	
	8H	24.3	24.7	24.8	25.2	25.7	24.6	25.0	25.1	25.5	26.1	

Luminance table		Max. for $\gamma \geq 65^\circ$		Photometric dimensions in mm:		L = 1500 B = 58	
C-planes	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°
γ	Luminance in cd/m²						
45°	38143.6	37669.5	39700.7	43242.7	41141.7	35261.7	32184.5
50°	29719.0	29176.8	29591.0	31794.9	31958.6	28425.2	25362.3
55°	23081.9	22159.3	21569.2	23053.4	24961.6	22766.8	19941.7
60°	18528.5	17217.6	16083.6	17215.7	19692.6	18212.1	16113.3
65°	15605.7	13969.5	12540.8	13489.7	15821.3	15178.2	13825.0
70°	13588.5	11866.5	10157.8	11045.7	13002.5	13255.1	12606.4
75°	11807.9	10015.7	8382.6	9183.9	10854.3	11790.2	11726.5
80°	10073.7	8254.4	6696.8	7332.6	8780.4	10060.1	10384.1
85°	7225.0	5844.8	4842.8	5381.6	6370.2	7515.4	7828.7

Photometric test report

Family
Licross® 11 Recessed

Order number: 51TE12DN4AXG3C
EAN: 4058352934746

LP number
58637_189

Luminance values in cd/m²

γ 65°


γ 70°

γ 75°

γ 80°

γ 85°

siteco



Photometric test report

Family Licross® 11 Recessed	Order number: 51TE12DN4AXG3C EAN: 4058352934746	LP number 58637_189
Dimming levels table		environmental temperature: 25°C
		siteco

Luminous flux %	Dimming level linear	Dimming level logarithmic	Luminous flux [lm]	Power consumption [W]
100	254	254	10240	60.5
95	240	252	9723	57.4
90	226	250	9198	54.2
85	213	248	8708	51.3
80	199	245	8176	48.2
75	186	243	7674	45.3
70	173	240	7172	42.3
65	160	237	6664	39.5
60	147	234	6151	36.6
55	134	231	5629	33.7
50	121	227	5106	31.0
45	109	223	4619	28.4
40	96	218	4083	25.7
35	84	213	3588	23.1
30	72	208	3088	20.7
25	60	201	2581	18.2
20	47	192	2030	15.4
15	35	181	1517	12.9
10	24	168	1042	10.6
5	12	142	517	8.2
2	4	102	167	6.6