


Photometric test report

Family Round 21 M	Order number: 51MR36FD0421B EAN: 4058352829851	LP number 59509_2
	Version surface-mounted and suspended luminaire, cover, opal, PMMA, symmetric extremely wide distribution, direct distribution, aluminium housing, black	serial documentation 08.11.2023
	Lamps LED 4000 K CRI ≥ 80	
	Controlgear ECG-DALI	
Rated values Net luminous flux = 7110 lm Power consumption = 54.8 W Luminous efficacy = 129.7 lm/W		



Luminous intensity in cd/klm C180-0 C270-90 **Imax: 376 cd/klm**



Classifications	
DIN 5040	A 4 0
CIE	N1=49 N2=80 N3=96 N4=100 N5=100

Luminaire light output ratios	
η_{LB}	100.0%
ϕ_u	100.0%
ϕ_o	0.0%

Measurement conditions
 DIN EN 13032 and DIN 5032

Photometric test report

Family Round 21 M	Order number: 51MR36FD0421B EAN: 4058352829851	LP number 59509_2
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C-planes γ	0° 180°	15°	30°	45°	60°	75°	90° 270°	Phi-zone	Total Phi-zone
		165° 195° 345°	150° 210° 330°	135° 225° 315°	120° 240° 300°	105° 255° 285°			
Luminous intensity in cd/klm							Luminous flux in lm/klm		
0°	375.8	375.8	375.8	375.8	375.8	375.8	375.8	2.2	2.2
5°	373.6	373.6	373.6	373.6	373.7	373.6	373.6	17.8	20.1
10°	367.1	367.0	367.1	367.1	367.2	367.1	367.2	34.9	55.0
15°	356.4	356.5	356.5	356.7	356.7	356.7	356.7	50.6	105.6
20°	342.0	342.1	342.1	342.4	342.4	342.5	342.5	64.2	169.8
25°	324.2	324.6	324.4	324.9	324.8	325.3	324.9	75.2	245.0
30°	303.7	304.3	303.9	304.6	304.5	305.2	304.6	83.4	328.5
35°	280.8	281.7	281.1	282.4	281.8	282.9	282.0	88.6	417.1
40°	256.2	257.4	256.5	258.0	257.2	258.5	257.4	90.7	507.8
45°	230.2	231.7	230.5	232.2	231.4	232.8	231.7	89.8	597.5
50°	203.5	204.9	203.8	205.4	204.7	206.0	204.9	86.0	683.6
55°	176.3	177.6	175.5	178.1	177.3	178.7	177.4	79.6	763.2
60°	148.1	149.5	147.4	150.0	149.0	150.6	149.2	70.8	834.0
65°	119.2	120.8	118.4	121.2	120.0	121.6	120.1	59.7	893.7
70°	89.7	91.5	88.8	91.9	90.4	92.3	90.6	46.8	940.5
75°	60.9	62.5	60.0	63.4	61.5	63.0	61.6	32.8	973.3
80°	34.5	35.9	33.5	36.8	35.0	36.0	35.0	19.1	992.4
85°	13.2	14.6	12.4	14.8	13.6	14.5	13.7	7.6	1000.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0

Photometric test report

Family Round 21 M	Order number: 51MR36FD0421B EAN: 4058352829851	LP number 59509_2
----------------------	---	----------------------

UGR-Table	Standard room	siteco
-----------	---------------	--------

Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions	View crosswise (C0)					View endwise (C90)					
x	y										
2H	2H	19.5	21.2	19.9	21.5	21.8	19.6	21.3	19.9	21.6	21.9
	3H	21.1	22.6	21.5	23.0	23.3	21.2	22.7	21.5	23.0	23.4
	4H	21.7	23.1	22.1	23.5	23.8	21.8	23.2	22.2	23.5	23.9
	6H	22.1	23.4	22.5	23.8	24.2	22.2	23.5	22.6	23.9	24.2
	8H	22.3	23.5	22.7	23.9	24.3	22.3	23.6	22.8	23.9	24.3
	12H	22.4	23.5	22.8	23.9	24.3	22.4	23.6	22.8	24.0	24.4
4H	2H	20.3	21.7	20.7	22.1	22.4	20.3	21.8	20.7	22.1	22.5
	3H	22.0	23.2	22.4	23.6	24.0	22.1	23.3	22.5	23.7	24.1
	4H	22.7	23.8	23.2	24.2	24.6	22.8	23.9	23.2	24.3	24.7
	6H	23.3	24.2	23.7	24.6	25.1	23.3	24.3	23.8	24.7	25.1
	8H	23.4	24.3	23.9	24.7	25.2	23.5	24.4	24.0	24.8	25.3
	12H	23.6	24.3	24.0	24.8	25.3	23.6	24.4	24.1	24.8	25.3
8H	4H	23.0	23.9	23.5	24.4	24.8	23.1	24.0	23.6	24.4	24.9
	6H	23.7	24.4	24.2	24.9	25.4	23.7	24.5	24.2	24.9	25.4
	8H	23.9	24.5	24.4	25.0	25.5	24.0	24.6	24.5	25.1	25.6
	12H	24.1	24.6	24.6	25.1	25.6	24.1	24.7	24.7	25.2	25.7
12H	4H	23.1	23.9	23.6	24.3	24.8	23.1	23.9	23.6	24.4	24.9
	6H	23.8	24.4	24.3	24.9	25.4	23.8	24.4	24.3	24.9	25.4
	8H	24.0	24.5	24.5	25.0	25.6	24.1	24.6	24.6	25.1	25.6

Luminance table	Max. for $\gamma \geq 65^\circ$	Photometric dimensions in mm:	D = 590
-----------------	---------------------------------	-------------------------------	---------

C-planes	γ	Luminance in cd/m ²							
		0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°	
45°		8465.8	8523.0	8478.3	8539.6	8510.0	8560.8	8521.7	
50°		8232.8	8291.3	8246.1	8310.5	8280.2	8335.7	8288.1	
55°		7992.7	8053.4	7958.9	8075.4	8036.9	8101.9	8044.9	
60°		7704.5	7777.9	7664.2	7803.5	7750.3	7832.1	7759.4	
65°		7334.8	7431.0	7282.8	7455.4	7381.6	7482.8	7391.7	
70°		6822.5	6960.9	6754.5	6986.7	6875.2	7015.2	6886.4	
75°		6124.0	6281.9	6030.4	6374.8	6183.3	6331.7	6191.4	
80°		5166.2	5369.5	5018.6	5511.6	5234.5	5391.9	5246.5	
85°		3944.1	4359.4	3703.6	4408.7	4063.4	4340.0	4090.3	

Photometric test report

Family
Round 21 M

Order number: 51MR36FD0421B
EAN: 4058352829851

LP number
59509_2

Luminance values in cd/m² γ 65° γ 70° γ 75° γ 80° γ 85° **siteco**

