


Photometric test report

Family Highbay 11	Order number: 51HN12DA4HBA EAN: 4069025440389	LP number 59710_354
	Version primary light control with lens, PMMA, housing, white, wide distribution Lamps LED 4000 K CRI ≥ 80 Controlgear ECG-DALI Setting DC mode (central or group accumulator) initial emergency light level Rated values Net luminous flux = 2890 lm Power consumption = 14.5 W Luminous efficacy = 199.3 lm/W	serial documentation 18.03.2025



Luminous intensity in cd/klm C180-0 C270-90 **Imax: 772 cd/klm**



Classifications	
DIN 5040	A 6 0
CIE	N1=88 N2=98 N3=100 N4=100 N5=100

Luminaire light output ratios	
η_{LB}	100.0%
ϕ_u	100.0%
ϕ_o	0.0%

Measurement conditions
DIN EN 13032 and DIN 5032

Photometric test report

Family Highbay 11	Order number: 51HN12DA4HBA EAN: 4069025440389	LP number 59710_354
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C-planes γ	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°	Luminous intensity in cd/klm		Luminous flux in lm/klm	
								Phi-zone	Total Phi-zone	Phi-zone	Total Phi-zone
0,0°	643.6	643.6	643.6	643.6	643.6	643.6	643.6	1.0	1.0	1.0	1.0
2,5°	644.5	645.1	645.0	644.3	644.2	643.7	641.7	7.7	8.7	7.7	8.7
5,0°	651.5	652.3	650.7	647.5	645.3	643.2	640.4	15.5	24.1	15.5	24.1
7,5°	669.6	669.1	664.2	657.2	651.2	645.8	641.3	23.5	47.6	23.5	47.6
10,0°	693.4	691.0	681.5	670.0	659.9	651.2	645.8	31.9	79.6	31.9	79.6
12,5°	711.8	709.4	700.3	685.9	671.9	660.7	654.0	40.7	120.2	40.7	120.2
15,0°	721.3	721.7	717.1	704.9	689.4	675.9	667.7	49.7	169.9	49.7	169.9
17,5°	743.8	740.8	737.9	726.5	708.9	693.0	684.2	59.4	229.3	59.4	229.3
20,0°	761.9	761.9	759.6	745.2	724.0	705.6	696.8	69.2	298.5	69.2	298.5
22,5°	772.0	771.2	770.0	754.7	731.1	710.8	702.6	78.2	376.7	78.2	376.7
25,0°	758.1	756.6	756.3	743.6	722.7	703.3	695.6	85.1	461.8	85.1	461.8
27,5°	706.7	709.5	709.5	700.0	685.7	672.3	667.0	87.8	549.7	87.8	549.7
30,0°	640.4	635.6	633.7	626.6	621.7	614.1	609.9	85.8	635.5	85.8	635.5
32,5°	530.6	537.6	535.6	526.2	530.2	524.1	520.8	78.1	713.6	78.1	713.6
35,0°	428.2	426.4	425.9	411.9	420.8	414.2	411.4	66.0	779.6	66.0	779.6
37,5°	322.5	323.4	327.0	311.0	319.4	310.8	308.2	53.0	832.6	53.0	832.6
40,0°	236.1	234.0	241.6	230.8	230.9	219.8	218.4	40.7	873.3	40.7	873.3
42,5°	162.3	165.3	172.9	171.1	161.7	151.3	150.8	30.2	903.5	30.2	903.5
45,0°	117.3	114.9	119.4	122.5	109.3	102.6	102.3	21.9	925.4	21.9	925.4
47,5°	80.5	81.4	82.8	85.5	75.2	71.4	70.8	15.9	941.3	15.9	941.3
50,0°	59.4	58.0	58.0	59.0	52.9	50.5	49.6	11.7	953.0	11.7	953.0
52,5°	43.3	42.8	42.8	43.0	39.3	37.2	36.6	8.9	961.8	8.9	961.8
55,0°	33.3	32.4	32.9	33.7	30.5	28.7	28.3	7.1	968.9	7.1	968.9
57,5°	25.9	25.4	25.9	26.8	24.5	22.9	22.9	5.8	974.7	5.8	974.7
60,0°	20.9	20.2	21.2	21.8	20.4	18.9	19.2	4.9	979.5	4.9	979.5
62,5°	16.9	16.2	17.4	18.0	17.2	15.9	16.4	4.1	983.6	4.1	983.6
65,0°	14.9	13.6	14.4	15.1	14.8	13.6	14.4	3.6	987.2	3.6	987.2
67,5°	12.3	11.4	12.5	12.4	13.0	11.7	12.6	3.1	990.3	3.1	990.3
70,0°	10.4	9.5	10.5	10.1	11.1	10.1	11.0	2.7	993.0	2.7	993.0
72,5°	8.2	7.7	7.9	8.2	8.7	8.6	9.5	2.2	995.2	2.2	995.2
75,0°	6.5	6.0	6.0	6.4	6.6	7.1	7.9	1.7	996.9	1.7	996.9
77,5°	4.5	4.3	4.4	4.7	5.1	5.6	6.3	1.3	998.2	1.3	998.2
80,0°	2.9	2.7	2.9	3.1	3.5	4.1	4.7	0.9	999.1	0.9	999.1
82,5°	1.3	1.4	1.6	1.8	2.2	2.7	3.3	0.5	999.7	0.5	999.7
85,0°	0.6	0.6	0.6	0.7	1.0	1.4	1.8	0.3	999.9	0.3	999.9
87,5°	0.3	0.3	0.3	0.3	0.3	0.4	0.5	0.1	1000.0	0.1	1000.0
90,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0	0.0	1000.0

Photometric test report

Family Highbay 11	Order number: 51HN12DA4HBA EAN: 4069025440389	LP number 59710_354
----------------------	--	------------------------

UGR-Table	Standard room	siteco	
-----------	---------------	--------	--

Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions	View crosswise (C0)					View endwise (C90)					
x	y										
2H	2H	14.2	15.5	14.6	15.8	16.1	13.9	15.2	14.3	15.5	15.8
	3H	14.2	15.3	14.6	15.7	16.0	13.9	15.1	14.3	15.4	15.7
	4H	14.2	15.2	14.6	15.6	16.0	13.9	15.0	14.3	15.3	15.7
	6H	14.2	15.1	14.6	15.5	15.9	14.0	14.9	14.4	15.3	15.7
	8H	14.2	15.0	14.7	15.4	15.8	14.1	14.9	14.5	15.2	15.7
	12H	14.2	14.9	14.6	15.3	15.8	14.1	14.8	14.5	15.2	15.6
4H	2H	14.1	15.1	14.5	15.5	15.9	13.8	14.8	14.2	15.2	15.6
	3H	14.1	15.0	14.6	15.4	15.8	13.9	14.7	14.3	15.1	15.5
	4H	14.1	14.9	14.6	15.3	15.7	13.9	14.7	14.4	15.1	15.5
	6H	14.1	14.8	14.6	15.2	15.7	14.0	14.6	14.4	15.1	15.5
	8H	14.1	14.7	14.6	15.1	15.6	14.0	14.6	14.5	15.0	15.5
	12H	14.1	14.6	14.6	15.0	15.5	14.0	14.5	14.5	15.0	15.5
8H	4H	14.1	14.6	14.5	15.1	15.6	13.9	14.4	14.3	14.9	15.4
	6H	14.0	14.5	14.5	15.0	15.5	13.9	14.4	14.4	14.9	15.4
	8H	14.0	14.4	14.5	14.9	15.4	13.9	14.3	14.4	14.8	15.4
	12H	14.0	14.3	14.5	14.8	15.4	14.0	14.3	14.5	14.8	15.3
12H	4H	14.1	14.5	14.6	15.0	15.5	13.9	14.3	14.4	14.8	15.3
	6H	14.0	14.4	14.6	14.9	15.4	13.9	14.3	14.4	14.8	15.3
	8H	14.0	14.3	14.5	14.8	15.4	13.9	14.2	14.5	14.8	15.3

Luminance table	Max. for $\gamma \geq 65^\circ$	Photometric dimensions in mm:	L = 426 B = 264
-----------------	---------------------------------	-------------------------------	--------------------

C-planes	γ	Luminance in cd/m ²								
		0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°		
45,0°		4263.7	4175.0	4339.8	4451.0	3970.9	3728.3	3717.3		
50,0°		2375.6	2319.4	2317.0	2358.4	2116.3	2017.8	1983.2		
55,0°		1492.9	1453.0	1473.7	1507.6	1367.6	1285.5	1270.1		
60,0°		1073.8	1036.6	1089.1	1121.8	1050.3	972.7	985.1		
65,0°		906.0	824.2	878.5	916.4	897.4	829.9	876.7		
70,0°		778.8	710.5	786.0	760.4	834.2	759.4	829.3		
75,0°		641.8	594.4	592.8	634.0	658.8	705.1	786.0		
80,0°		433.3	404.3	427.8	462.2	521.6	613.5	699.4		
85,0°		173.1	172.2	177.8	208.2	307.8	410.1	531.3		

Photometric test report

Family Highbay 11	Order number: 51HN12DA4HBA EAN: 4069025440389	LP number 59710_354
-----------------------------	--	-------------------------------

Luminance values in cd/m²
γ 65°
γ 70°
γ 75°
γ 80°
γ 85°
siteco

