

Photometric test report

Family
Highbay 21

Order number: 52HN11DA4HLA01
EAN: 4069025421241

LP number
59724_162



Version primary light control with lens, PMMA, housing, white, for Licross® rail, narrow distribution, with multisensor node BT

Lamps LED 4000 K | CRI ≥ 80

Controlgear ECG-DALI

Rated values Net luminous flux = 19000 lm
Power consumption = 99.4 W
Luminous efficacy = 191.2 lm/W

serial
documentation
20.03.2025


siteco

Luminous intensity in cd/klm

C180-0

C270-90

Imax: 2719 cd/klm



Classifications

DIN 5040 A 7 0
CIE N1=89 N2=97 N3=99
N4=100 N5=100

Luminaire light output ratios

η_{LB} 100.0%
 ϕ_u 100.0%
 ϕ_o 0.0%

Measurement conditions

DIN EN 13032 and DIN 5032

Photometric test report

Family Highbay 21	Order number: 52HN11DA4HLA01 EAN: 4069025421241	LP number 59724_162
Table of values for luminous intensities		Maximum luminous intensity

sitEco

C- planes	0,0° 180,0°	7,5° 172,5° 187,5° 352,5°	15,0° 165,0° 195,0° 345,0°	22,5° 157,5° 202,5° 337,5°	30,0° 150,0° 210,0° 330,0°	37,5° 142,5° 217,5° 322,5°	45,0° 135,0° 225,0° 315,0°
		Luminous intensity in cd/klm					
γ							
0,0°	2718.5	2718.5	2718.5	2718.5	2718.5	2718.5	2718.5
2,5°	2662.8	2671.1	2671.1	2670.6	2667.6	2663.3	2662.4
5,0°	2502.8	2490.9	2498.0	2494.5	2487.6	2479.1	2473.3
7,5°	2228.4	2233.8	2227.9	2223.2	2214.7	2203.4	2194.2
10,0°	1915.8	1894.8	1902.8	1897.9	1890.8	1880.8	1870.9
12,5°	1554.6	1560.7	1554.3	1552.6	1548.0	1540.2	1531.7
15,0°	1246.2	1237.0	1237.4	1238.4	1237.7	1233.9	1229.0
17,5°	947.1	964.7	959.6	960.0	960.5	959.5	958.4
20,0°	765.0	752.2	754.6	751.6	749.0	747.8	747.5
22,5°	591.2	598.6	590.3	583.2	577.5	573.8	572.1
25,0°	481.4	472.8	470.4	460.9	451.8	445.8	443.1
27,5°	370.5	376.3	371.1	363.9	355.1	347.9	344.8
30,0°	301.2	297.9	295.0	290.6	284.7	279.0	275.2
32,5°	234.8	237.8	234.9	232.8	229.2	225.3	220.4
35,0°	189.2	188.5	187.7	186.9	184.4	180.6	175.3
37,5°	154.0	153.7	151.7	151.0	148.4	144.9	141.0
40,0°	125.7	123.3	123.0	121.9	119.1	115.8	113.2
42,5°	99.2	100.3	99.3	98.6	95.9	92.9	90.7
45,0°	81.4	79.6	79.7	79.0	77.2	74.6	72.7
47,5°	64.2	64.9	64.5	64.0	62.8	60.9	59.5
50,0°	52.5	51.6	51.8	51.7	51.0	49.9	49.1
52,5°	41.7	41.9	41.8	42.1	41.9	41.4	40.9
55,0°	33.9	33.5	34.1	34.8	35.0	35.0	34.7
57,5°	27.1	27.4	28.1	29.2	29.7	29.7	29.6
60,0°	22.3	22.3	23.0	24.6	25.8	25.8	25.5
62,5°	19.0	19.2	19.6	20.7	22.4	22.3	22.0
65,0°	17.0	16.8	17.2	18.3	19.8	19.1	19.1
67,5°	14.7	14.8	14.9	16.1	17.2	16.3	16.1
70,0°	12.8	12.5	12.6	13.8	14.3	13.8	13.9
72,5°	11.3	11.1	10.9	11.6	11.4	11.2	11.7
75,0°	9.7	9.3	8.9	9.6	9.3	9.1	9.3
77,5°	7.4	7.4	7.1	7.5	7.1	6.8	7.1
80,0°	4.9	4.7	4.8	4.8	4.5	4.5	4.8
82,5°	2.2	2.3	2.3	2.4	2.4	2.5	2.7
85,0°	0.8	0.8	0.8	0.8	0.8	0.9	1.0
87,5°	0.4	0.4	0.4	0.4	0.4	0.4	0.4

Photometric test report

Family Highbay 21	Order number: 52HN11DA4HLA01 EAN: 4069025421241	LP number 59724_162
Table of values for luminous intensities		Maximum luminous intensity

siteco

C- planes	52,5° 127,5° 232,5° 307,5°	60,0° 120,0° 240,0° 300,0°	67,5° 112,5° 247,5° 292,5°	75,0° 105,0° 255,0° 285,0°	82,5° 97,5° 262,5° 277,5°	90,0° 270,0°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm						Luminous flux in lm/klm	
0,0°	2718.5	2718.5	2718.5	2718.5	2718.5	2718.5	4.1	4.1
2,5°	2661.4	2660.0	2657.7	2657.0	2651.0	2647.2	31.8	35.9
5,0°	2468.0	2461.9	2456.3	2452.9	2444.7	2440.4	59.1	95.0
7,5°	2185.5	2176.0	2168.0	2162.0	2152.6	2148.3	78.5	173.5
10,0°	1860.3	1847.8	1837.7	1831.0	1822.1	1817.6	88.9	262.4
12,5°	1522.0	1510.4	1500.7	1495.5	1488.9	1485.2	90.6	353.0
15,0°	1223.0	1215.3	1207.9	1204.2	1200.8	1197.6	86.8	439.8
17,5°	955.3	949.4	945.6	944.9	945.8	944.0	78.6	518.5
20,0°	745.4	741.8	741.4	743.7	748.0	747.7	70.2	588.6
22,5°	571.4	571.2	573.5	575.9	579.7	580.1	60.8	649.4
25,0°	443.2	444.5	446.3	448.3	449.2	448.8	52.5	701.9
27,5°	344.0	344.5	345.1	346.1	344.9	343.6	44.7	746.7
30,0°	273.7	273.8	273.9	272.4	270.2	268.2	38.5	785.2
32,5°	217.7	217.2	215.9	213.7	211.0	209.4	32.9	818.1
35,0°	172.5	170.5	168.2	166.4	165.0	164.5	27.8	845.9
37,5°	138.1	135.6	133.3	132.0	130.7	130.3	23.7	869.5
40,0°	110.2	108.1	106.1	104.8	103.7	103.1	20.0	889.6
42,5°	88.5	86.8	85.0	83.9	83.2	82.7	16.9	906.5
45,0°	71.2	69.8	68.4	67.3	66.9	66.6	14.2	920.7
47,5°	58.5	57.3	56.0	55.1	54.8	54.6	12.1	932.8
50,0°	48.3	47.1	46.0	45.5	45.1	44.8	10.3	943.0
52,5°	40.2	39.3	38.3	37.7	37.1	36.8	8.7	951.8
55,0°	34.1	33.4	32.5	31.7	31.0	30.7	7.5	959.3
57,5°	29.3	29.0	28.2	27.0	26.3	26.1	6.6	965.9
60,0°	25.7	25.8	24.8	23.5	22.8	22.6	5.8	971.6
62,5°	22.4	22.9	21.8	20.7	20.1	19.9	5.1	976.8
65,0°	19.6	20.2	19.7	18.4	17.9	17.8	4.6	981.4
67,5°	16.7	17.6	17.8	16.4	16.0	16.0	4.1	985.5
70,0°	14.1	15.0	15.6	14.4	14.4	14.6	3.6	989.1
72,5°	11.7	12.4	13.4	12.9	13.2	13.4	3.1	992.3
75,0°	9.5	10.4	12.0	11.4	11.8	11.9	2.7	995.0
77,5°	7.2	8.1	9.6	9.6	10.0	10.2	2.1	997.1
80,0°	5.1	5.7	7.0	7.5	7.6	8.0	1.5	998.6
82,5°	3.0	3.6	4.5	5.0	5.3	5.6	0.9	999.5
85,0°	1.2	1.7	2.3	2.7	3.1	3.3	0.4	999.9
87,5°	0.4	0.4	0.5	0.6	0.8	0.9	0.1	1000.1


Photometric test report

Family Highbay 21			Order number: 52HN11DA4HLA01 EAN: 4069025421241							LP number 59724_162	
UGR-Table			Standard room							siteco	
Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		View crosswise (C0)					View endwise (C90)				
x	y										
2H	2H	17.4	18.6	17.8	18.9	19.2	16.9	18.0	17.2	18.3	18.7
	3H	17.9	18.8	18.2	19.2	19.5	17.5	18.5	17.9	18.9	19.2
	4H	18.1	19.0	18.5	19.3	19.7	18.0	18.9	18.4	19.2	19.6
	6H	18.3	19.1	18.7	19.4	19.8	18.4	19.2	18.8	19.5	19.9
	8H	18.4	19.0	18.8	19.4	19.8	18.6	19.3	19.0	19.7	20.1
	12H	18.3	18.9	18.8	19.3	19.7	18.7	19.3	19.1	19.7	20.1
4H	2H	17.6	18.5	18.0	18.9	19.2	17.1	18.0	17.5	18.4	18.8
	3H	18.2	18.9	18.6	19.3	19.8	18.0	18.7	18.4	19.1	19.5
	4H	18.5	19.2	18.9	19.6	20.0	18.5	19.2	19.0	19.6	20.0
	6H	18.7	19.3	19.2	19.7	20.2	19.1	19.6	19.5	20.0	20.5
	8H	18.8	19.2	19.2	19.7	20.2	19.2	19.7	19.7	20.2	20.7
	12H	18.8	19.2	19.3	19.6	20.1	19.4	19.8	19.9	20.3	20.8
8H	4H	18.6	19.1	19.1	19.5	20.0	18.6	19.1	19.1	19.6	20.0
	6H	18.9	19.3	19.4	19.7	20.3	19.2	19.6	19.7	20.1	20.6
	8H	18.9	19.2	19.4	19.7	20.3	19.4	19.8	20.0	20.3	20.8
	12H	18.9	19.2	19.4	19.7	20.2	19.6	19.9	20.2	20.4	21.0
12H	4H	18.6	19.0	19.1	19.5	20.0	18.6	19.0	19.1	19.5	20.0
	6H	18.9	19.2	19.4	19.7	20.2	19.2	19.5	19.7	20.0	20.6
	8H	18.9	19.2	19.4	19.7	20.2	19.5	19.7	20.0	20.2	20.8

Luminance table		Max. for $\gamma \geq 65^\circ$		Photometric dimensions in mm:				L = 426 B = 264		
C-planes	0,0° 180,0°	10,0° 170,0° 190,0° 350,0°	20,0° 160,0° 200,0° 340,0°	30,0° 150,0° 210,0° 330,0°	40,0° 140,0° 220,0° 320,0°	50,0° 130,0° 230,0° 310,0°	60,0° 120,0° 240,0° 300,0°	70,0° 110,0° 250,0° 290,0°	80,0° 100,0° 260,0° 280,0°	90,0° 270,0°
		Luminance in cd/m²								
γ										
45,0°		19446.3	18984.0	18958.6	18447.4	17653.6	17127.2	16686.0	16243.1	16012.8
50,0°		13785.4	13555.1	13614.8	13401.6	13040.9	12786.8	12380.8	12027.2	11880.1
55,0°		9985.9	9890.7	10191.5	10323.1	10277.2	10096.7	9846.0	9495.7	9175.2
60,0°		7544.7	7592.6	8137.8	8733.3	8678.7	8662.3	8722.2	8257.5	7769.3
65,0°		6811.0	6754.3	7137.5	7897.1	7614.3	7748.8	8080.6	7738.2	7218.4
70,0°		6316.7	6179.4	6673.2	7048.8	6797.9	6886.9	7413.8	7600.2	7100.6
75,0°		6314.0	5975.3	6190.2	6077.1	5931.6	6135.0	6763.1	7888.4	7654.2
80,0°		4766.3	4585.5	4714.8	4419.9	4459.9	4791.1	5579.6	7076.6	7313.2
85,0°		1566.2	1526.2	1560.4	1583.7	1751.2	2124.5	3248.8	4683.6	5770.6
										6429.7

Photometric test report

Family Highbay 21	Order number: 52HN11DA4HLA01 EAN: 4069025421241	LP number 59724_162
Luminance values in cd/m²		siteco
		γ 65° γ 70° γ 75° γ 80° γ 85°



Photometric test report

Family Highbay 21	Order number: 52HN11DA4HLA01 EAN: 4069025421241	LP number 59724_162
Dimming levels table		environmental temperature: 25°C



Luminous flux %	Dimming level linear	Dimming level logarithmic	Luminous flux [lm]	Power consumption [W]
100	254	254	19000	99.4
95	241	252	18066	94.3
90	228	250	17132	89.2
85	214	248	16116	83.7
80	201	245	15171	78.6
75	188	243	14217	73.6
70	175	240	13264	68.6
65	163	238	12376	63.9
60	150	235	11412	58.9
55	137	231	10438	53.8
50	124	228	9465	48.8
45	112	224	8563	44.2
40	99	219	7581	39.3
35	87	215	6670	34.7
30	74	209	5679	29.9
25	62	202	4759	25.4
20	50	194	3836	20.9
15	37	183	2829	16.0
10	25	169	1899	11.5
5	13	145	966	6.8
2	5	110	342	3.6