


Photometric test report

Family Silica® 21 Floor	Order number: 51MX53DA4ZM00982XX EAN: 4069025333858	LP number 59648_11
	Version	floorstanding uplight, with homogeneous illumination, prismatic cover, indirect-/ direct distribution, extremely wide distribution, with presence- and daylightsensor
	Lamps	LED 4000 K CRI ≥ 80
	Controlgear	ECG-DALI
	Setting	individual position: only indirect light
	Rated values	Net luminous flux = 10000 lm Power consumption = 60.5 W Luminous efficacy = 165.3 lm/W
		serial documentation 09.04.2025
		siteco



Classifications		Luminaire light output ratios	
DIN 5040	E 1 2	η_{LB}	100.0%
CIE	N1=0 N2=0 N3=0	ϕ_u	0.3%
	N4=0 N5=100	ϕ_o	99.7%

Measurement conditions
DIN EN 13032 and DIN 5032

Photometric test report

Family Silica® 21 Floor	Order number: 51MX53DA4ZM00982XX EAN: 4069025333858	LP number 59648_11
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C- planes	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm							Luminous flux in lm/klm	
0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
10°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
15°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
20°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
25°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.9	0.9	0.9	0.8	0.7	0.7	0.7	0.4	0.4
90°	11.5	11.2	11.8	11.6	6.9	2.4	0.9	4.6	5.0
95°	53.3	54.6	58.7	55.5	35.6	18.2	9.4	23.1	28.1
100°	95.6	98.1	99.0	86.8	58.3	33.0	21.6	39.0	67.1
105°	138.1	140.4	137.2	117.3	80.1	49.7	36.5	54.0	121.1
110°	184.0	185.7	173.9	143.9	103.1	67.2	52.3	68.0	189.1
115°	224.6	223.0	205.9	169.1	125.1	85.0	69.1	79.1	268.2
120°	259.0	254.8	232.1	190.2	145.4	102.1	86.4	86.8	355.0
125°	281.2	275.1	248.8	207.4	162.0	118.7	104.6	90.2	445.2
130°	289.3	283.0	256.4	219.1	175.3	134.9	123.1	89.2	534.4
135°	288.3	283.0	259.3	227.1	186.9	150.6	141.4	85.4	619.8
140°	284.1	280.3	260.5	231.9	196.2	165.7	158.7	79.6	699.4
145°	279.2	276.5	259.8	234.5	203.5	179.7	174.6	72.4	771.8
150°	272.8	270.9	256.5	235.2	209.8	192.5	189.0	63.8	835.5
155°	265.0	263.6	251.0	233.7	215.0	203.7	201.5	54.1	889.6
160°	254.9	254.0	243.6	231.0	219.4	213.1	211.9	43.6	933.2
165°	242.9	242.8	235.7	229.0	223.3	220.4	220.2	32.7	965.9
170°	233.7	234.5	230.6	228.3	226.5	225.7	226.1	21.8	987.7
175°	229.9	230.9	228.6	228.5	228.4	228.9	229.7	10.9	998.6
180°	229.0	229.0	229.0	229.0	229.0	229.0	229.0	1.4	1000.0

Photometric test report

Family Silica® 21 Floor	Order number: 51MX53DA4ZM00982XX EAN: 4069025333858	LP number 59648_11
UGR-Table	Standard room	siteco

The UGR formula for this luminaire type cannot be used, see LiTG Publication 20:
"The UGR - Process for Evaluation of Direct Glare of Artificial Lighting in Indoor Rooms"

Luminance table	Max. for $\gamma \geq 65^\circ$	Photometric dimensions in mm:	L = 1200 B = 50
-----------------	---------------------------------	----------------------------------	--------------------

C- planes	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°
γ	Luminance in cd/m²						
45°	0.0	0.0	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	1774.6	1723.0	1636.9	1483.9	1348.2	1262.1	1262.1

Photometric test report

Family
Silica® 21 Floor

Order number: 51MX53DA4ZM00982XX
EAN: 4069025333858

LP number
59648_11

Luminance values in cd/m²

γ 65°


γ 70°

γ 75°

γ 80°

γ 85°

siteco



Photometric test report

Family Silica® 21 Floor	Order number: 51MX53DA4ZM00982XX EAN: 4069025333858	LP number 59648_11
Dimming levels table		environmental temperature: 25°C



Luminous flux %	Dimming level linear	Dimming level logarithmic	Luminous flux [lm]	Power consumption [W]
100	254	254	10000	60.5
95	240	252	9484	57.1
90	227	250	9002	54.0
85	214	248	8516	50.9
80	200	245	7990	47.8
75	187	243	7495	44.6
70	174	240	6997	41.7
65	161	237	6497	38.7
60	148	234	5990	35.6
55	135	231	5481	32.6
50	123	227	5008	29.9
45	110	223	4490	26.9
40	98	219	4009	24.2
35	85	214	3486	21.3
30	73	208	3000	18.6
25	61	202	2509	15.9
20	49	194	2018	13.5
15	36	182	1482	10.7
10	24	168	985	8.0
5	12	142	484	5.1
2	5	110	191	3.4