

Photometric test report

Family
Monsun® 11

Order number: 51FF40MP380L
EAN: 4069025611871

LP number
59020_12



Version prismatic diffuser, opal, PMMA, impact resistant, wide distribution
Lamps LED 3000 K | CRI ≥ 80
Controlgear ECG Multilumen
Rated values Net luminous flux = 8080 lm
Power consumption = 45.1 W
Luminous efficacy = 179.2 lm/W

serial
documentation
13.11.2025


siteco

Luminous intensity in cd/klm

C180-0

C270-90

Imax: 338 cd/klm



Classifications

DIN 5040 A 4 1
CIE N1=47 N2=77 N3=93
N4=95 N5=100

Luminaire light output ratios

η_{LB} 100.0%
 ϕ_u 94.8%
 ϕ_o 5.2%

Measurement conditions

DIN EN 13032 and DIN 5032

Photometric test report

Family Monsun® 11	Order number: 51FF40MP380L EAN: 4069025611871	LP number 59020_12
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C- planes	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm							Luminous flux in lm/klm	
0°	337.3	337.3	337.3	337.3	337.3	337.3	337.3	2.0	2.0
5°	337.5	336.4	334.5	335.8	337.2	336.9	336.9	16.1	18.1
10°	332.2	331.9	329.8	331.2	333.0	332.9	332.8	31.6	49.7
15°	324.3	324.6	322.6	323.9	325.4	325.8	325.7	46.0	95.7
20°	313.1	314.1	312.1	313.6	315.1	315.7	315.9	58.9	154.6
25°	297.5	298.9	297.5	299.8	301.9	302.4	303.0	69.5	224.1
30°	279.2	281.0	279.9	281.8	284.8	285.5	286.5	77.5	301.6
35°	257.9	260.0	259.0	261.1	264.4	265.2	266.6	82.4	384.0
40°	236.2	237.9	236.5	237.1	240.1	242.3	243.9	84.2	468.2
45°	213.3	214.4	212.9	211.4	213.4	215.8	217.9	82.9	551.1
50°	190.1	190.6	188.8	186.3	185.4	186.8	189.1	78.9	630.0
55°	164.5	165.1	164.4	160.2	157.7	156.9	158.8	72.3	702.3
60°	138.1	138.1	137.0	134.7	130.2	127.4	128.2	63.3	765.6
65°	117.3	116.4	112.4	108.2	104.2	99.4	98.8	53.7	819.3
70°	100.3	99.0	91.7	84.5	79.3	73.6	71.6	44.1	863.5
75°	83.2	81.7	74.7	65.1	57.1	50.8	47.3	34.8	898.3
80°	65.8	64.5	59.3	48.9	38.3	30.8	26.4	25.9	924.2
85°	49.5	48.3	44.5	35.6	23.7	15.0	10.1	17.9	942.1
90°	37.1	36.3	33.4	26.4	15.8	6.7	2.1	12.6	954.7
95°	29.4	28.9	27.0	22.0	13.4	5.0	1.8	10.2	964.9
100°	23.9	23.5	21.8	17.7	11.0	3.7	1.6	8.1	973.0
105°	20.2	19.6	17.9	14.3	8.4	2.4	1.4	6.5	979.5
110°	17.5	16.7	15.0	11.5	6.2	1.4	1.2	5.2	984.7
115°	15.3	14.5	12.7	9.2	4.4	1.2	1.1	4.2	988.8
120°	13.2	12.3	10.5	7.1	2.9	1.2	1.0	3.2	992.1
125°	11.0	10.1	8.2	5.1	1.7	1.1	1.0	2.4	994.5
130°	8.6	7.8	6.1	3.4	1.3	1.0	1.0	1.7	996.2
135°	6.4	5.7	4.2	2.0	1.3	1.0	1.0	1.2	997.3
140°	4.2	3.7	2.5	1.6	1.3	1.1	1.1	0.7	998.1
145°	2.4	2.1	1.8	1.6	1.3	1.1	1.1	0.5	998.6
150°	1.9	1.8	1.7	1.5	1.2	1.2	1.2	0.4	999.0
155°	1.7	1.7	1.6	1.5	1.3	1.3	1.3	0.3	999.4
160°	1.6	1.6	1.5	1.3	1.3	1.3	1.3	0.3	999.6
165°	1.3	1.3	1.3	1.3	1.3	1.3	1.3	0.2	999.8
170°	1.3	1.3	1.3	1.3	1.3	1.3	1.3	0.1	999.9
175°	1.3	1.3	1.3	1.3	1.3	1.4	1.4	0.1	1000.0
180°	1.3	1.3	1.3	1.3	1.3	1.3	1.3	0.0	1000.0

Photometric test report

Family Monsun® 11		Order number: 51FF40MP380L EAN: 4069025611871							LP number 59020_12	
UGR-Table		Standard room							siteco	
Reflection factor of ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5
Reflection factor of walls		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3
Reflection factor of floor		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		View crosswise (C0)					View endwise (C90)			
x	y									
2H	2H	21.0	22.7	21.4	23.0	23.3	21.3	23.0	21.6	23.3
	3H	22.6	24.2	23.0	24.5	24.9	22.6	24.1	23.0	24.5
	4H	23.4	24.9	23.8	25.2	25.6	23.1	24.5	23.5	24.9
	6H	24.2	25.5	24.6	25.9	26.3	23.4	24.8	23.8	25.1
	8H	24.6	25.8	25.0	26.2	26.6	23.5	24.8	24.0	25.2
	12H	24.9	26.0	25.3	26.4	26.8	23.6	24.8	24.0	25.2
4H	2H	21.7	23.1	22.1	23.5	23.9	21.9	23.4	22.3	23.7
	3H	23.5	24.8	23.9	25.1	25.5	23.4	24.6	23.8	25.0
	4H	24.5	25.6	24.9	26.0	26.4	24.0	25.1	24.4	25.5
	6H	25.4	26.4	25.8	26.8	27.2	24.4	25.4	24.9	25.9
	8H	25.8	26.7	26.3	27.1	27.6	24.6	25.5	25.0	25.9
	12H	26.2	27.0	26.7	27.5	27.9	24.7	25.5	25.2	26.0
8H	4H	24.8	25.7	25.2	26.1	26.6	24.4	25.3	24.8	25.7
	6H	25.9	26.6	26.3	27.1	27.6	24.9	25.7	25.4	26.2
	8H	26.4	27.1	26.9	27.6	28.1	25.1	25.8	25.6	26.3
	12H	26.9	27.5	27.5	28.0	28.6	25.3	25.9	25.8	26.4
12H	4H	24.8	25.6	25.3	26.1	26.6	24.5	25.3	24.9	25.7
	6H	26.0	26.6	26.5	27.1	27.6	25.1	25.7	25.6	26.2
	8H	26.6	27.1	27.1	27.6	28.2	25.3	25.9	25.8	26.4

Luminance table		Max. for $\gamma \geq 65^\circ$		Photometric dimensions in mm:		L = 1590 B = 87	H(C0) = 21 H(C90) = 21	H(C180) = 21 H(C270) = 21
C-planes	γ	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°
			Luminance in cd/m²					
45°		14195.7	14320.2	14465.8	14798.5	15573.8	16581.0	17767.4
50°		13412.9	13508.5	13650.9	13941.5	14556.3	15579.0	16918.4
55°		12457.4	12566.2	12796.6	12976.1	13506.6	14425.4	15875.7
60°		11375.9	11447.7	11654.5	11993.0	12376.2	13162.5	14637.8
65°		10686.8	10672.4	10623.8	10792.8	11224.8	11827.0	13285.2
70°		10299.4	10251.2	9834.0	9653.2	9936.0	10414.1	11801.0
75°		9876.4	9798.1	9339.5	8786.5	8632.0	8942.8	10175.1
80°		9349.5	9267.0	8974.0	8136.5	7364.4	7253.3	8249.6
85°		8819.5	8747.9	8610.0	7799.1	6333.1	5398.2	5853.7

Photometric test report

Family
Monsun® 11

Order number: 51FF40MP380L
EAN: 4069025611871

LP number
59020_12

Luminance values in cd/m²

γ 65°


γ 70°

γ 75°

γ 80°

γ 85°

siteco



Photometric test report

Family Monsun® 11	Order number: 51FF40MP380L EAN: 4069025611871	LP number 59020_12
Multilumen Table	environmental temperature: 25°C	siteco

DIP-Step	Switch Setting			Luminous flux [lm]	Power consumption [W]
	1	2	3		
1	A	C	E	8080	45.1
2	A	C	F	7510	41.6
3	A	D	E	6850	37.6
4	A	D	F	6270	34.1
5	B	C	E	5670	30.7
6	B	C	F	5050	27.2
7	B	D	E	4440	23.8
8	B	D	F	4130	22.1