Photometric test report

Family
Highbay 41



Order number: 51HD3XMBMN0A
EAN: 4069025768841

Version	cover panel, PC, clear, adjustable light distribution, adjustable color temperature: 4000K | 5000K | 6500K
Lamps	LED 5000 K | CRI ≥ 80
Controlgear	ECG Multilumen
Setting	individual position: wide distribution, Lumen Max.
Rated values	Net luminous flux = 32900 lm Power consumption = 188.0 W Luminous efficacy = 175 lm/W


LP number
60292_2

serial documentation
30.07.2026

siteco

Luminous intensity in cd/klm C180-0

Imax: 566 cd/klm



Classifications

DIN 5040	A 5 0
CIE	N1=67 N2=93 N3=99 N4=100 N5=100

Luminaire light output ratios

ηLB	100.0%
ϕ_u	100.0%
ϕ_o	0.0%

Measurement conditions

DIN EN 13032 and DIN 5032

Photometric test report

Family	Order number: 51HD3XMBMN0A	LP number
Highbay 41	EAN: 4069025768841	60292_2

siteco

Table of values for luminous intensities

Maximum luminous intensity

C-planes	0°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm	Luminous flux in lm/klm	
0°	566.4	3.4	3.4
5°	561.9	26.8	30.2
10°	546.2	52.0	82.2
15°	523.5	74.3	156.5
20°	495.0	92.8	249.3
25°	458.8	106.3	355.6
30°	416.0	114.0	469.6
35°	370.2	116.4	586.0
40°	313.6	110.5	696.5
45°	245.3	95.1	791.5
50°	168.1	70.6	862.1
55°	107.5	48.3	910.4
60°	69.6	33.0	943.4
65°	45.5	22.6	966.0
70°	29.1	15.0	981.0
75°	19.0	10.1	991.1
80°	11.0	5.9	997.0
85°	4.8	2.6	999.7
90°	0.6	0.3	1000.0
95°	0.0	0.0	1000.0
100°	0.0	0.0	1000.0
105°	0.0	0.0	1000.0
110°	0.0	0.0	1000.0
115°	0.0	0.0	1000.0
120°	0.0	0.0	1000.0
125°	0.0	0.0	1000.0
130°	0.0	0.0	1000.0
135°	0.0	0.0	1000.0
140°	0.0	0.0	1000.0
145°	0.0	0.0	1000.0
150°	0.0	0.0	1000.0
155°	0.0	0.0	1000.0
160°	0.0	0.0	1000.0
165°	0.0	0.0	1000.0
170°	0.0	0.0	1000.0
175°	0.0	0.0	1000.0
180°	0.0	0.0	1000.0

Photometric test report

Family	Order number: 51HD3XMBMN0A	LP number
Highbay 41	EAN: 4069025768841	60292_2

siteco

UGR-Table

Standard room

Reflection factor of ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Reflection factor of walls		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reflection factor of floor		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions			View crosswise (C0)					View endwise (C90)			
x	y										
2H	2H	27.8	29.3	28.1	29.6	29.9	27.8	29.3	28.1	29.6	29.9
	3H	28.1	29.4	28.5	29.8	30.1	28.1	29.4	28.5	29.8	30.1
	4H	28.3	29.5	28.7	29.8	30.2	28.3	29.5	28.7	29.8	30.2
	6H	28.3	29.5	28.8	29.8	30.2	28.3	29.5	28.8	29.8	30.2
	8H	28.4	29.4	28.9	29.8	30.2	28.4	29.4	28.9	29.8	30.2
	12H	28.4	29.4	28.9	29.8	30.2	28.4	29.4	28.9	29.8	30.2
4H	2H	28.0	29.2	28.4	29.5	29.9	28.0	29.2	28.4	29.5	29.9
	3H	28.4	29.4	28.8	29.8	30.2	28.4	29.4	28.8	29.8	30.2
	4H	28.6	29.5	29.0	29.9	30.3	28.6	29.5	29.0	29.9	30.3
	6H	28.8	29.5	29.2	30.0	30.4	28.8	29.5	29.2	30.0	30.4
	8H	28.8	29.5	29.3	30.0	30.4	28.8	29.5	29.3	30.0	30.4
	12H	28.9	29.5	29.4	29.9	30.4	28.9	29.5	29.4	29.9	30.4
8H	4H	28.7	29.4	29.1	29.8	30.3	28.7	29.4	29.1	29.8	30.3
	6H	28.9	29.4	29.4	29.9	30.4	28.9	29.4	29.4	29.9	30.4
	8H	28.9	29.4	29.4	29.9	30.5	28.9	29.4	29.4	29.9	30.5
	12H	29.0	29.4	29.5	29.9	30.5	29.0	29.4	29.5	29.9	30.5
12H	4H	28.7	29.3	29.2	29.7	30.2	28.7	29.3	29.2	29.7	30.2
	6H	28.9	29.4	29.4	29.8	30.4	28.9	29.4	29.4	29.8	30.4
	8H	29.0	29.4	29.5	29.9	30.4	29.0	29.4	29.5	29.9	30.4

Luminance table

Max. for $\gamma >= 65°$

Photometric dimensions in mm: D = 288

C-planes	0°
γ	Luminance in cd/m²
45°	175209.8
50°	132054.8
55°	94625.7
60°	70314.9
65°	54351.6
70°	43009.6
75°	37166.5
80°	32021.2
85°	27895.3

Photometric test report

Family	Order number: 51HD3XMBMN0A	LP number
Highbay 41	**EAN: 4069025768841**	**60292_2**

Luminance values in cd/m²

γ 65° γ 70° γ 75° γ 80° γ 85°

