

Order No.: 5MD53003S | GTIN (EAN): 4058352327166

Product description: Rond21sens,HF-sens,rec



Rondel 21 multi-sensor, installation type: recessed, installation location: in the luminaire, of PC, protection rating (complete): IP40, insulation class (complete): insulation class II (safety insulation), certification: CE, voltage: 220..240V, voltage type: AC, 1 x HF movement sensor, 1 x light sensor, packaging unit: 1 piece

IP 40 IK 03  

Wt. (kg): 0.5
GTIN (EAN): 4058352327166



Order No.: 5MD53003S | GTIN (EAN): 4058352327166

Detailed technical description: Rond21sens,HF-sens,rec



Key data

- Product type: sensor
- Product name: Rondel 21
- Order No.: 5MD53003S

Certificates, Standards

- Protection rating: IP40
- Insulation class: insulation class II (safety insulation)
- Impact resistance: IK03
- Temperature range (operation): 0..+40°C
- Standard: EN 60598-2-22
- Certification, designation: CE

Material, Colour

- housing: PC, graphite (RAL 7037)
- Colour specification: graphite (RAL 7037)

Mounting

- Mounting method, mounting location: recessed, in the luminaire
- Mounting height: 2.5..6m

Electrical connection

- Connection: terminal, 2-pole
- Nominal voltage: 220..240V, 50Hz, AC
- Stand-by power consumption: max. 0.5W

Dimensions, Weight

- Diameter: 266mm
- Height: 24mm
- Weight: 0.5kg

Inputs

1x HF movement sensor

- Detection range: D max= 12m (at mounting height h= 6m), depending on direction and intensity of movement
- Option: switching time adjustable between 5 seconds - 30 minutes
- Feature: for motion detection, circular detection area

1x light sensor

- Option: daylight threshold adjustable from 2..50lx

Order No.: 5MD53003S | GTIN (EAN): 4058352327166

Dimensions: Rond21sens, HF-sens, rec

24 | | 28

