

Order No.: 5TR305FCMA | GTIN (EAN): 4058352635704

Product description: Mod31Intbasemod



Modario® 31 Interface MD, master, local control, dimmable,
installation location: to the Modario® trunking rail, of sheet steel, protection
rating (complete): IP20, insulation class (complete): insulation class I
(protective earthing), certification: CE, VDE, voltage: 230V, voltage type: AC, 1
x DALI, packaging unit: 1 piece

 IP 20  

Wt. (kg): 0.4
GTIN (EAN): 4058352635704

Order No.: 5TR305FCMA | GTIN (EAN): 4058352635704

Detailed technical description: Mod31Intbasemod



Key data

- System family: SITECO Connect 31 Logistic DALI
- Product type: base module
- Product name: Modario® 31 Interface
- Order No.: 5TR305FCMA

Lighting technology | Lamps | Control gear

Component 1

Lamps:

- Supplement: halogen-free wiring

Operating device:

- Control: DALI, dimmable

Certificates, Standards

- Protection rating: IP20
- Insulation class: insulation class I (protective earthing)
- Temperature range (operation): -20..+50°C
- Certification, designation: CE, VDE

Material, Colour

- trunking rail adapter set: sheet steel, coil coated, white
- Colour specification: white

Mounting

- Supplement: only suitable for indoor use

Electrical connection

- Connection: plug, 5-pole, with phase selection
- Nominal voltage: 230V, 50Hz, AC

Dimensions, Weight

- Length: 500mm
- Width: 96mm
- Height: 97mm
- Weight: 0.4kg

Outputs

DALI

- Feature: DALI, master function, broadcast addressing, max. 30 DALI ECGs

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.com)

Tolerances related to thermal, electrical and photometric data according to IEC 62722

Issued 16.02.2024 - Modifications and errors subject to change - Ensure that you always use the latest version -