

### Order No.: 59UA1LT | GTIN (EAN): 4058352419618 Product description: SConAuspkr,surf



SITECO Connect Audio, speaker, installation type: surface-mounted, 2-way speaker, rated input power: 10W, housing, rectangular, rounded, of plastic, white, length: 80mm, width: 210mm, height: 330mm, protection rating (complete): IP20, insulation class (complete): insulation class II (safety insulation), certification: CE, permissible operating ambient temperature: -10..+50°C, standard: UL 94-V0, EN 54-24, packaging unit: 1 piece

IP 20 🗌 🤆

Wt. (kg): 1.4 GTIN (EAN): 4058352419618

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.com) Tolerances related to thermal, electrical and photometric data according to IEC 62722 Issued 09.04.2025 - Modifications and errors subject to change - Ensure that you always use the latest version -

# ѕітесо

## Order No.: 59UA1LT | GTIN (EAN): 4058352419618 Detailed technical description: SConAuspkr,surf



#### Key data

- System family: Licross<sup>®</sup>
- Product type: speaker
- Product name: SITECO Connect Audio
- Order No.: 59UA1LT

# Lighting technology | Lamps | Control gear

#### **Component 1**

#### Lamps:

- Rated input power: 10W
- Supplement: incl. 1x speaker socket, 2x wall fastening screw, 1x terminal block (with thermal fuse), power adaption 10W, 5W, 3W, 1W

#### **Certificates, Standards**

- Protection rating: IP20
- Insulation class: insulation class II (safety insulation)
- Temperature range (operation): -10..+50°C
- Standard: EN 54-24, UL 94-V0
- Certification, designation: CE

#### Material, Colour

- housing: plastic, white, rectangular, rounded
- Colour specification: white

#### Mounting

 Mounting method, mounting location: surface-mounted, to the wall, in the Licross<sup>®</sup> trunking rail, to speaker insert

#### **Dimensions, Weight**

- Length: 80mm
- Width: 210mm
- Height: 330mm
- Weight: 1.4kg