

Order No.: 56TL1M | GTIN (EAN): 4058352400609 Product description: Lic,multiadapter,sh.steel,wh



Licross[®], rail insert, adapter, with plug, 5-pole, with phase selection, mains connection: 230V, AC, 50/60Hz, terminal,5-pole, max. 2.5mm², multi adapter, of sheet steel, coil coated, white, for IP20/IP40 protection rating, length: 500mm, width: 64mm, height: 68mm, multifunctional insert, protection rating (complete): IP20, insulation class (complete): insulation class I (protective earthing), certification: CE, UKCA, packaging unit: 1 piece

IP 20 🔔 🤆

Wt. (kg): 0.4 GTIN (EAN): 405835

4058352400609

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.com) Tolerances related to thermal, electrical and photometric data according to IEC 62722 Issued 09.04.2025 - Modifications and errors subject to change - Ensure that you always use the latest version -

ѕітесо

Order No.: 56TL1M | GTIN (EAN): 4058352400609 Detailed technical description: Lic,multiadapter,sh.steel,wh



Key data

- System family: Licross[®]
- Product type: rail insert
- Product name: Licross[®]
- Order No.: 56TL1M

Lighting technology | Lamps | Control gear

Component 1

Lamps:

 Supplement: internal wiring halogenfree, for trunking rail, 7..14-core, max. 0.5A

Certificates, Standards

- Protection rating: IP20
- Insulation class: insulation class I (protective earthing)
- Certification, designation: CE, UKCA

Material, Colour

- multi adapter: sheet steel, coil coated, white, for IP20/IP40 protection rating
- Colour specification: white

Mounting

 Supplement: only suitable for use in indoor areas

Electrical connection

- Connection: plug, 5-pole, with phase selection
- Nominal voltage: 230V, 50/60Hz, AC

Dimensions, Weight

- Length: 500mm
- Width: 64mm
- Height: 68mm
- Weight: 0.4kg