

Order No.: 5TR305FCSA | **GTIN (EAN):** 4058352635711

Product description: Mod31Intsens



Modario® 31 Interface Interface S, slave, local control - self-sufficient standalone sensors, central control - connection to lighting or building management, dimmable, installation location: to the Modario® trunking rail, of sheet steel, protection rating (complete): IP20, insulation class (complete): insulation class I (protective earthing), certification: CE, VDE, 1 x DALI-2, packaging unit: 1 piece



Wt. (kg): 0.4
GTIN (EAN): 4058352635711

Order No.: 5TR305FCSA | **GTIN (EAN):** 4058352635711

Detailed technical description: Mod31Intsens



Key data

- System family: Siteco Connect 11, SITECO Connect 21
- Product type: sensor
- Product name: Modario® 31 Interface
- Order No.: 5TR305FCSA

Lighting technology | Lamps | Control gear

Component 1

Lamps:

- Supplement: internal wiring halogen-free

Operating device:

- Control: DALI 2, dimmable

Certificates, Standards

- Protection rating: IP20
- Insulation class: insulation class I (protective earthing)
- Temperature range (operation): -20...+50°C
- Certification, designation: CE, VDE

Material, Colour

- trunking rail adapter set: sheet steel, coil coated, white
- Colour specification: white

Mounting

- Supplement: only suitable for use in indoor areas

Electrical connection

- Connection: plug, 5-pole, with phase selection

Dimensions, Weight

- Length: 597mm
- Width: 96mm
- Height: 97mm
- Weight: 0.4kg

Outputs

DALI-2

- Feature: DALI, slave function, DALI current max. 6mA