

**Order No.:** 5EA3CM000001 | **GTIN (EAN):** 4058352571590

**Product description:** SConWi,SmartPlugCellular



SITECO Connect WirelessSmart Plug Cellular, luminaire controller, communication: local mesh radio network, EGPRS, NB-IoT NB2, LTE Cat M1, 5G, 4G, 2G, 2.4GHz, D4i type A, control: remote setup and operation, local setting and operation with USB stick, local setting and operation with smartphone app, manual, by time, by timer, by weekday, by AstroDim calendar, by daylight, via API, with radio clock, optionally via radio push button, sensor technology: GALILEO, GLONASS, GNSS, GPS, inclination sensor, temperature sensor, daylight sensor, The usage fees for remote access via web application and mobile communications (LTE CAT M1 / NB IoT NB2 / EGPRS) are included in the scope of delivery with a term of 5 years. This individually extendable runtime starts when the device QR code is scanned into a system, Smart Interface below and above, Logarithmic DALI dimming curve preset. Can be switched to linear via software, installation type: screw fastening, installation location: to the luminaire, Smart Interface above: Zhaga, Smart Interface below: Zhaga, of PBT, voltage: 24V, voltage type: DC, protection rating (complete): IP66, certification: CE, packaging unit: 1 piece

IP 66 

Wt. (kg): 0.1  
GTIN (EAN): 4058352571590

**Order No.:** 5EA3CM000001 | **GTIN (EAN):** 4058352571590

**Detailed technical description:** SConWi,SmartPlugCellular



#### Key data

- System family: SITECO Connect 31 Wireless
- Product type: luminaire controller
- Product name: SITECO Connect Wireless
- Order No.: 5EA3CM000001

#### Lighting technology | Lamps | Control gear

#### Component 1

#### Operating device:

- Control: D4i, Smart Interface below and above, The usage fees for remote access via web application and mobile communications (LTE CAT M1 / NB IoT NB2 / EGPRS) are included in the scope of delivery with a term of 5 years. This individually extendable runtime starts when the device QR code is scanned into a system, Logarithmic DALI dimming curve preset. Can be switched to linear via software

#### Certificates, Standards

- Protection rating: IP66
- Temperature range (operation): -40..+85°C
- Standard: according to Zhaga book 18
- Certification, designation: CE

#### Material, Colour

- housing: PBT, transparent, colour-backed, transparent
- Colour specification: transparent

#### Mounting

- Mounting method, mounting location: screw fastening, to the luminaire

#### Electrical connection

- Nominal voltage: 24V, DC

#### Dimensions, Weight

- Diameter: 80mm
- Height: 46mm
- Weight: 0.1kg