

# Order No.: 5EA6TEF03 | GTIN (EAN): 4058352495681

# **Product description:** SLC, Servicebox



Street Light Control, Siteco® Service Box, control gear: DALI, control: digital communication interface, Bluetooth 4.0, with system connector: plug/socket, 4-pole, DC, housing, of plastic, dark grey, Siteco® Service Box, control via: Siteco Digital Interface, protection rating (complete): IP54, insulation class (complete): insulation class II (safety insulation), certification: CE, permissible operating ambient temperature for outdoor applications: 0..+50°C, packaging unit: 1 piece

IP 54 □ (€

Wt. (kg): 3.5

GTIN (EAN): 4058352495681



# Order No.: 5EA6TEF03 | GTIN (EAN): 4058352495681

# **Detailed technical description:** SLC, Servicebox



#### Key data

- Product type: Siteco® Service BoxProduct name: Street Light Control
- Order No.: 5EA6TEF03

# Lighting technology | Lamps | Control gear

## Component 1

#### Lamps:

 Supplement: with ON/OFF switch, with connection cable, battery operation 4x

#### **Operating device:**

- Control: DALI
- Equipment: digital communication interface, Bluetooth 4.0

## Certificates, Standards

- Protection rating: IP54
- Insulation class: insulation class II (safety insulation)
- Temperature range (operation): 0..+50°C
- Certification, designation: CE

#### Material, Colour

- housing: plastic, dark grey
- Colour specification: dark grey

#### **Electrical connection**

- Connection: system connector: plug/socket, 4-pole
- Battery supply: incl. 4x Mignon AA/LR6 batteries
- Feature: external power supply 5LZ905402 needed

## **Dimensions, Weight**

- Weight: 3.5kg

#### **Outputs**

### 1x SDI (Siteco® Digital Interface)

- Connection: pin terminal
- Feature: operational status display

## 1x status LED

Feature: status LED

# Software

- Required software: iQ app

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.com)
Tolerances related to thermal, electrical and photometric data according to IEC 62722
Issued 09.04.2025 - Modifications and errors subject to change - Ensure that you always use the latest version -