

Order No.: 59LJ201 | GTIN (EAN): 4058352612361

Product description: Ecopack31 multisens,PIR-sens,surf



Ecopack® 31, multi-sensor, installation type: surface-mounted, housing, of PC/ABS, traffic white (RAL 9016), length: 149mm, width: 56mm, height: 28mm, PIR sensor, protection rating (complete): IP20, insulation class (complete): insulation class II (safety insulation), certification: CE, impact resistance: IK02, permissible operating ambient temperature: -10..+35°C, packaging unit: 1 piece

IP 20  

Wt. (kg): 0.1
GTIN (EAN): 4058352612361

Order No.: 59LJ201 | GTIN (EAN): 4058352612361

Detailed technical description: Ecopack31multisens,PIR-sens,surf

Key data

- Product type: multi-sensor
- Product name: Ecopack® 31
- Order No.: 59LJ201

Certificates, Standards

- Protection rating: IP20
- Insulation class: insulation class II (safety insulation)
- Impact resistance: IK02
- Temperature range (operation): -10..+35°C
- Certification, designation: CE

Material, Colour

- housing: PC/ABS, traffic white (RAL 9016)
- Colour specification: traffic white (RAL 9016)

Mounting

- Mounting method, mounting location: surface-mounted, to the luminaire

Dimensions, Weight

- Length: 149mm
- Width: 56mm
- Height: 28mm
- Weight: 0.1kg

Service life

- Rated service life: 50000h at AT = 25°C

Inputs

1x PIR movement sensor

- Option: switching time adjustable between 5 seconds - 30 minutes
- Feature: for motion detection, circular detection area

1x light sensor

- Option: daylight threshold adjustable from 2..50lx