

Order No.: 5LZ925602 | **GTIN (EAN):** 4058352364062

Product description: SConpresencedet,PIR-sens,surf



SITECO Connectmulti-sensor PS2, master, local control - self-sufficient standalone sensors, dimmable, installation type: surface-mounted, installation location: to the ceiling, of plastic, protection rating (complete): IP20, insulation class (complete): insulation class II (safety insulation), certification: CE, VDE, voltage: 220..240V, voltage type: AC, 1 x PIR movement sensor, 4 x push button input, 1 x 1 x light sensor, 1 x DALI, packaging unit: 1 piece



Wt. (kg): 0.3
GTIN (EAN): 4058352364062

Order No.: 5LZ925602 | **GTIN (EAN):** 4058352364062

Detailed technical description: SConpresencedet,PIR-sens,surf



Key data

- System family: SITECO Connect 31 Education
- Product type: presence detector
- Product name: SITECO Connect
- Order No.: 5LZ925602

Lighting technology | Lamps | Control gear

Component 1

Lamps:

- Rated input power: 0.5W

Operating device:

- Control: DALI, dimmable

Certificates, Standards

- Protection rating: IP20
- Insulation class: insulation class II (safety insulation)
- Temperature range (operation): 0..+40°C
- Certification, designation: CE, VDE

Material, Colour

- housing: plastic, pure white (RAL 9010)
- Colour specification: pure white (RAL 9010)

Mounting

- Mounting method, mounting location: surface-mounted, to the ceiling
- Mounting height: 2.5..10m
- Supplement: only suitable for use in indoor areas

Electrical connection

- Nominal voltage: 220..240V, 50/60Hz, AC

Dimensions, Weight

- Length: 120mm
- Width: 120mm
- Height: 65mm
- Weight: 0.3kg

Inputs

1x PIR movement sensor

- Connection: PIR sensor (passive-infrared)
- Detection angle: 360°
- Detection range: radial min./max. 5x 5m/11x 11m, tangential min./max. 6x 6m/28x 28m
- Detection range: min./max. 4.8x 4.8m/8.2x 8.2m
- Feature: square detection area

4x push button input

- Feature: operating mode: full or semi automatic


Outputs

1x DALI

- Feature: grouping of luminaires in window, corridor or blackboard, integrated DALI power supply 150mA

Order No.: 5LZ925602 | GTIN (EAN): 4058352364062

Dimensions: SConpresencedet,PIR-sens,surf



Sensor IR Quattro HD/ PS2

Mh	R	T	P
3m	4x4m - 8x8m	4x4m - 22x22m	4x4m - 8x8m
3,5m	5x5m - 11x11m	6x6m - 28x28m	7,2x7,2m - 8,2x8,2m

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.com)

Tolerances related to thermal, electrical and photometric data according to IEC 62722

Issued 09.04.2025 - Modifications and errors subject to change - Ensure that you always use the latest version -