

**Order No.:** 5LZ905950 | **GTIN (EAN):** 4058352668863

**Product description:** SCon21H,controller,wired



SITECO Connect 21Hcontroller, master, central control - connection to lighting or building management, dimmable, installation type: recessed, installation location: in an electrical distributor, of plastic, part units: 6 part units, protection rating (complete): IP20, insulation class (complete): insulation class I (protective earthing), certification: CE, UKCA, voltage: 100..240V, voltage type: AC, 1 x network connector Ethernet, 1 x USB/WiFi, 3 x service push button, 4 x DALI-2, 1 x status LED, packaging unit: 1 piece

IP 20  

Wt. (kg): 0.5  
GTIN (EAN): 4058352668863

**Order No.:** 5LZ905950 | **GTIN (EAN):** 4058352668863

**Detailed technical description:** SCon21H,controller,wired



#### Key data

- System family: SITECO Connect 21H
- Product type: control unit
- Product name: SITECO Connect 21H
- Order No.: 5LZ905950

#### Lighting technology | Lamps | Control gear

#### Component 1

#### Operating device:

- Control: DALI 2, dimmable

#### Certificates, Standards

- Protection rating: IP20
- Insulation class: insulation class I (protective earthing)
- Temperature range (operation): 0..+40°C
- Certification, designation: CE, UKCA

#### Material, Colour

- housing: plastic, bright grey, 6 part units
- Colour specification: bright grey

#### Mounting

- Mounting method, mounting location: recessed, in an electrical distributor
- Supplement: only suitable for use in indoor areas

#### Electrical connection

- Nominal voltage: 100..240V, 50/60Hz, AC

#### Dimensions, Weight

- Length: 91mm
- Width: 107mm
- Height: 62mm
- Weight: 0.5kg

#### Inputs

#### 3x service push button

- Option: for manual control and basic system setting

#### Outputs

#### 4x DALI-2

- System current: DALI current 250mA per DALI line
- Feature: maximum 64 ECG DALI and maximum 63 certified DALI2 sensors/push button interfaces connectable per DALI line, HCLlive function in combination with ECG DT8, averaging with connected light sensors, connection of DALI2 certified sensors